

Novachem Pty Ltd

Version No: 3.3

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: **12/09/2018** Print Date: **12/09/2018** S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Cannabigerol (CBG)	
Chemical Name	cannabigerol	
Synonyms	C-141	
Proper shipping name	METHANOL	
Other means of identification	Not Available	
CAS number	25654-31-3*	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Laboratory chemicals, Manufacture of substances

Details of the supplier of the safety data sheet

	A
Registered company name	Novachem Pty Ltd
Address	25 Crissane Road, Heidelberg West Victoria 3081 Australia
Telephone	+61384151255
Fax	+61386250088
Website	www.novachem.com.au
Email	novachem@novachem.com.au
Telephone Fax Website	+61384151255 +61386250088 www.novachem.com.au

Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre
Emergency telephone numbers	13 11 26
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	S9	
Classification ^[1]	Flammable Liquid Category 2, Acute Toxicity (Oral) Category 3, Acute Toxicity (Dermal) Category 3, Acute Toxicity (Inhalation) Category 3, Specific target organ toxicity - single exposure Category 1	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements

	Hazard pictogram(s)
	Hazard pictogram(s)

SIGNAL WORD

DANGER

Hazard statement(s)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs.

Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P270	Do not eat, drink or smoke when using this product.	
P271	Use only outdoors or in a well-ventilated area.	

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
P307+P311	IF exposed: Call a POISON CENTER or doctor/physician.	
P330	Rinse mouth.	
P363	Wash contaminated clothing before reuse.	

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.
------	---

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

CAS No	%[weight]	Name
67-56-1	99.9	methanol
25654-31-3	0.1	cannabigerol

Mixtures

See section above for composition of Substances

SECTION 4 FIRST AID MEASURES

Description	of	first	aid	measures
-------------	----	-------	-----	----------

Eye Contact	 If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Quickly but gently, wipe material off skin with a dry, clean cloth. Immediately remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise: INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. NOTE: Wear a protective glove when inducing vomiting by mechanical means. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

For acute and short term repeated exposures to methanol:

[•] Toxicity results from accumulation of formaldehyde/formic acid.

- Clinical signs are usually limited to CNS, eyes and GI tract Severe metabolic acidosis may produce dyspnea and profound systemic effects which may become intractable. All symptomatic patients should have arterial pH measured. Evaluate airway, breathing and circulation.
- Stabilise obtunded patients by giving naloxone, glucose and thiamine.
- Decontaminate with Ipecac or lavage for patients presenting 2 hours post-ingestion. Charcoal does not absorb well; the usefulness of cathartic is not established.
- Forced diuresis is not effective; haemodialysis is recommended where peak methanol levels exceed 50 mg/dL (this correlates with serum bicarbonate levels below 18 meq/L).
- Ethanol, maintained at levels between 100 and 150 mg/dL, inhibits formation of toxic metabolites and may be indicated when peak methanol levels exceed 20 mg/dL. An intravenous solution of ethanol in D5W is optimal.
- Folate, as leucovorin, may increase the oxidative removal of formic acid. 4-methylpyrazole may be an effective adjunct in the treatment. 8. Phenytoin may be preferable to diazepam for controlling seizure.

[Ellenhorn Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

Determinant	Index	Sampling Time	Comment
1. Methanol in urine	15 mg/l	End of shift	B, NS
2. Formic acid in urine	80 mg/gm creatinine	Before the shift at end of workweek	B, NS

B: Background levels occur in specimens collected from subjects **NOT** exposed.

NS: Non-specific determinant - observed following exposure to other materials.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Water may be an ineffective extinguishing media for methanol fires; static explosions are reported for aqueous solutions as dilute as 30%. Water may be used to cool containers.

- Alcohol stable foam.Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	• Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. Combustion products include: carbon dioxide (CO2) formaldehyde other pyrolysis products typical of burning organic material.
HAZCHEM	•2WE

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions f	for safe	handling
---------------	----------	----------

 Safe handling

 Containers, even those that have been emptied, may contain explosive vapours.
 Do NOT cut, drill, grind, weld or perform similar operations on or near containers.

	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 NOTE: Special security requirements may be mandated under Federal/State Regulation(s). Store in original containers. Store in vault fitted with warning devices or detectors recommended by various Federal/State authorities. Store in vault used only for the purpose of storage of drugs of addiction.

Conditions for safe storage, including any incompatibilities

Suitable container	 Packaging as recommended by manufacturer. Check that containers are clearly labelled. Tamper-proof containers. Polyethylene or polypropylene containers. Glass container is suitable for laboratory quantities For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) For manufactured product having a viscosity of at least 250 cSt.
Storage incompatibility	 Methanol: reacts violently with strong oxidisers, acetyl bromide, alkyl aluminium salts, beryllium dihydride, bromine, chromic acid, 1-chloro-3,3-diffuoro-2-methoxycyclopropene, cyanuric chloride, diethylzinc, isophthaloyl chloride, nitric acid, perchloric acid, potassium-tert-butoxide, potassium sulfur diimide, Raney nickel catalysts, 2,4,6-trichlorotriazine, triethylaluminium, 1,3,3-trifluoro-2-methoxycyclopropene is incompatible with strong acids, strong caustics, alkaline earth and alkali metals, aliphatic amines, acetaldehyde, benzoyl peroxide, 1,3-bis(din-n-cyclopentadienyl iron)-2-propen-1-one, calcium carbide, chloroform, chromic anhydride, chromium trioxide, dialkylzinc, dichlorine oxide, dichloromethane, ethylene oxide, hypochlorous acid, isocyanates, isopropyl chlorocarbonate, lithium tetrahydroaluminate, magnesium, methyl azide, nitrogen dioxide, palladium, pentafluoroguanidine, perchloryl fluoride, phosphorus pentasulfide, phosphorus trioxide, potassium, tangerine oil, triisobutylaluminium mixtures with lead perchlorate, sodium hypochlorite are explosive may react with metallic aluminium may generate electrostatic charges, due to low conductivity, on flow or agitation attacks some plastics, rubber and coatings. Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content Alcohols are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents. reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkytzincs, dichlorine oxide, phypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus haildes, phosphorus partasulfide, tangerine oil, tittef

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA									
Source	Ingredient	Material name	TWA		STEL		Peak		Notes
Australia Exposure Standards	methanol	Methyl alcohol	200 ppm /	262 mg/m3	328 mg/m	3 / 250 ppm	Not Availa	ble	Not Available
EMERGENCY LIMITS									
Ingredient	Material name			TEEL-1		TEEL-2		TEEL-3	

Ingredient	Material name	TEEL-1		TEEL-2	TEEL-3
methanol	Methyl alcohol; (Methanol)	thyl alcohol; (Methanol) Not Available		Not Available	Not Available
Ingredient	Original IDLH		Revised I	DLH	
methanol	6,000 ppm		Not Available		
cannabigerol	Not Available		Not Availa	ble	

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	 Safety glasses with side shields Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

Cannabigerol	(CBG)
--------------	-------

Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the $\ computer-generated$ selection:

Cannabigerol (CBG)

Material	CPI
BUTYL	A
BUTYL/NEOPRENE	A
PE/EVAL/PE	А
PVDC/PE/PVDC	А
SARANEX-23 2-PLY	A
SARANEX-23	А
TEFLON	А
VITON/NEOPRENE	А
NEOPRENE	В
NAT+NEOPR+NITRILE	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
PVA	С
PVC	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise

be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	0.79 @ 20 C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	385- (464 ICI)
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-97.8	Viscosity (cSt)	0.59
Initial boiling point and boiling range (°C)	64-65	Molecular weight (g/mol)	32.04
Flash point (°C)	11-12(16.1 OC)	Taste	Not Available

Respiratory protection

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Continued...

Cannabigerol (CBG)

Evaporation rate	2.1 BuAc=1 BuAC = 1	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	36	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	6	Volatile Component (%vol)	ca 100 @ 20 C
Vapour pressure (kPa)	12.26 @ 20 C	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Neutral
Vapour density (Air = 1)	1.1	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content. Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	There is strong evidence to suggest that this material can cause, if inhaled once, very serious, irreversible damage of organs. The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Minor but regular methanol exposures may effect the central nervous system, optic nerves and retinae. Symptoms may be delayed, with headache, fatigue, nausea, blurring of vision and double vision. Continued or severe exposures may cause damage to optic nerves, which may become severe with permanent visual impairment even blindness resulting. WARNING : Methanol is only slowly eliminated from the body and should be regarded as a cumulative poison which cannot be made non-harmful [<i>CCINFO</i>] Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects. There is strong evidence to suggest that this material can cause, if inhaled once, serious, irreversible damage of organs.		
Ingestion	Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Methanol may produce a burning or painful sensation in the mouth, throat, chest, and stomach. This may be accompanied by nausea, vomiting, headache, dizziness, shortness of breath, weakness, fatigue, leg cramps, restlessness, confusion, drunken behaviour, visual disturbance, drowsiness, com and death.		
Skin Contact	Skin contact with the material may produce toxic effects; systemic effects may result following absorption. The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. There is strong evidence to suggest that this material, on a single contact with skin, can cause serious, irreversible damage of organs.		
Eye	Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). 510meth		
	Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. Liver and/or kidney injury may also result.		
Chronic	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer	m, may produce cumulative effects characterised by gastrointestinal	
Chronic	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer	m, may produce cumulative effects characterised by gastrointestinal	
	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer	m, may produce cumulative effects characterised by gastrointestinal	
Chronic Cannabigerol (CBG)	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer Liver and/or kidney injury may also result.	m, may produce cumulative effects characterised by gastrointestinal nbling, unsteady gait, vertigo, conjunctivitis and clouded or double vision.	
	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer Liver and/or kidney injury may also result.	m, may produce cumulative effects characterised by gastrointestinal nbling, unsteady gait, vertigo, conjunctivitis and clouded or double vision.	
	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer Liver and/or kidney injury may also result.	m, may produce cumulative effects characterised by gastrointestinal nbling, unsteady gait, vertigo, conjunctivitis and clouded or double vision.	
Cannabigerol (CBG)	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer Liver and/or kidney injury may also result.	m, may produce cumulative effects characterised by gastrointestinal nbling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. IRRITATION Not Available	
	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer Liver and/or kidney injury may also result. TOXICITY Not Available	m, may produce cumulative effects characterised by gastrointestinal nbling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. IRRITATION Not Available IRRITATION	
Cannabigerol (CBG)	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer Liver and/or kidney injury may also result. TOXICITY Not Available TOXICITY Dermal (rabbit) LD50: 15800 mg/kg ^[2] Dermal (rabbit) LD50: 15800 mg/kg ^[2]	m, may produce cumulative effects characterised by gastrointestinal nbling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. IRRITATION Not Available IRRITATION Eye (rabbit): 100 mg/24h-moderate	
Cannabigerol (CBG)	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer Liver and/or kidney injury may also result. TOXICITY Not Available	m, may produce cumulative effects characterised by gastrointestinal nbling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. IRRITATION Not Available Eye (rabbit): 100 mg/24h-moderate Eye (rabbit): 40 mg-moderate Skin (rabbit): 20 mg/24 h-moderate	
Cannabigerol (CBG)	Long-term exposure to methanol vapour, at concentrations exceeding 3000 pp disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trer Liver and/or kidney injury may also result. TOXICITY Not Available TOXICITY Dermal (rabbit) LD50: 15800 mg/kg ^[2] Inhalation (rat) LC50: 63926.976 mg/l/4h ^[2]	m, may produce cumulative effects characterised by gastrointestinal nbling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. IRRITATION Not Available IRRITATION Eye (rabbit): 100 mg/24h-moderate Eye (rabbit): 40 mg-moderate	

Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances METHANOL The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. CANNABIGEROL In animal testing, cannabinoids (found in marijuana) caused changes in behaviour, hyperactivity, and seizures. High doses has caused delayed death. Long-term effects included central nervous system depression, showing as inco-ordination, decreased activity and generalized depression, with prolonged exposure leading to development of tolerance and symptoms of central nervous system stimulation, characterized by irritability, hypersensitivity, excessive activity, aggression, tremor and convulsions. Animals showed impaired specific motor and learning skills. No significant acute toxicological data identified in literature search. Acute Toxicity Carcinogenicity Q Skin Irritation/Corrosion Q Carcinogenicity Q

Acute Toxicity	•	Carcinogenicity	0
Skin Irritation/Corrosion	\otimes	Reproductivity	\odot
Serious Eye Damage/Irritation	\otimes	STOT - Single Exposure	×
Respiratory or Skin sensitisation	\otimes	STOT - Repeated Exposure	\otimes
Mutagenicity	\otimes	Aspiration Hazard	\otimes
		✓ - L	Pata available but does not fill the criteria for classification Pata available to make classification Pata Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Cannabigerol (CBG)	ENDPOINT	TEST DURATION (HR)		SPECIES	VALUE		SOURCE	
Califiabigeror (CDC)	Not Available	Not Available		Not Available	Not Avail	able	Not Availab	le
	ENDPOINT	TEST DURATION (HR)	SPECIE	S		VALUE	SO	URCE
	LC50	96	Fish			>100mg/L	4	
	EC50	48	Crustac	ea		>10000mg/L	4	
methanol	EC50	96	Algae o	r other aquatic plants		<10000mg/L	4	
	BCF	24	Algae o	r other aquatic plants		0.05mg/L	4	
	EC0	168	Algae o	r other aquatic plants		=530mg/L	1	
	NOEC	72	Crustac	ea		0.1mg/L	4	
	ENDPOINT	TEST DURATION (HR)		SPECIES	VALUE		SOURCE	
cannabigerol	Not Available	Not Available		Not Available	Not Avail	able	Not Availab	le
Legend:		ICLID Toxicity Data 2. Europe ECHA F oxicity Data (Estimated) 4. US EPA, E	•	•				

For Methanol: Log Kow: -0.82 to -0.66; Koc: 1; Henry s Law Constant: 4.55x10-6 atm-cu m/mole; Vapor Pressure: 127 mm Hg; BCF: < 10.

Atmospheric Fate: Methanol is expected to exist solely as a vapor in the ambient atmosphere. Vapor-phase methanol is broken down in the atmosphere by reactions with hydroxyl radicals; the half-life for this reaction in air is estimated to be 17 days.

Terrestrial Fate: Methanol is expected to have very high mobility in soil.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
methanol	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
methanol	LOW (BCF = 10)

Mobility in soil

Ingredient	Mobility
methanol	HIGH (KOC = 1)

SECTION 13 DISPOSAL CONSIDERATIONS

Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: F If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. • Where possible retain label warnings and SDS and observe all notices pertaining to the product. Valuable substance, hold all residues for recovery. Disposal of the material must be carried out in accordance with the requirements of the relevant Federal/State Act(s) or Code(s) regulating the disposal of Drugs of Addiction. Consult manufacturer/supplier for recycling options. Decontaminate empty containers with water; incinerate plastic bags. Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked. A Hierarchy of Controls seems to be common - the user should investigate: Reduction Product / Packaging disposal Reuse Recycling ۲ Disposal (if all else fails) This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. • DO NOT allow wash water from cleaning or process equipment to enter drains. It may be necessary to collect all wash water for treatment before disposal. • In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first. • Where in doubt contact the responsible authority. Recycle wherever possible. · Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. > Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material). Decontaminate empty containers.

SECTION 14 TRANSPORT INFORMATION

Marine Pollutant

Labels Required

ne Pollutant	NO
HAZCHEM	•2WE

Land transport (ADG)

UN number	1230
UN proper shipping name	METHANOL
Transport hazard class(es)	Class 3 Subrisk 6.1
Packing group	l
Environmental hazard	Not Applicable
Special precautions for user	Special provisions 279 Limited quantity 1 L

Air transport (ICAO-IATA / DGR)

UN number	1230			
UN proper shipping name	Methanol			
	ICAO/IATA Class	3		
Transport hazard class(es)	ICAO / IATA Subrisk	6.1		
	ERG Code	3L		
Packing group	11			
Environmental hazard	Not Applicable			
	Special provisions		A113	
Special precautions for user Cargo Only Packing Ins Cargo Only Maximum Q Special precautions for user Passenger and Cargo N Passenger and Cargo N Passenger and Cargo L	Cargo Only Packing Instructions		364	
	Qty / Pack	60 L		
	Passenger and Cargo Packing Instructions		352	
	Passenger and Cargo Maximum Qty / Pack		1L	
	Passenger and Cargo Limited Quantity Packing Instructions		Y341	
	Passenger and Cargo Limited Maximum Qty / Pack		1 L	

Sea transport (IMDG-Code / GGVSee)

UN number	1230
UN proper shipping name	METHANOL
Transport hazard class(es)	IMDG Class 3 IMDG Subrisk 6.1
Packing group	II
Environmental hazard	Not Applicable
Special precautions for user	EMS NumberF-E , S-DSpecial provisions279Limited Quantities1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

METHANOL(67-56-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)

CANNABIGEROL(25654-31-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS Not Applicable

National Inventory Status

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix	
F (Part 3)	
Averaging Other development for the Lipsforms Cale advisory of Manifestrate and Designers (CLICND). Cale advis	

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

National Inventory	Status
Australia - AICS	N (cannabigerol)
Canada - DSL	N (cannabigerol)
Canada - NDSL	N (methanol; cannabigerol)
China - IECSC	N (cannabigerol)
Europe - EINEC / ELINCS / NLP	N (cannabigerol)
Japan - ENCS	N (cannabigerol)
Korea - KECI	N (cannabigerol)
New Zealand - NZIoC	N (cannabigerol)
Philippines - PICCS	N (cannabigerol)
USA - TSCA	N (cannabigerol)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	12/09/2018
Initial Date	28/11/2017

Other information

Ingredients with multiple cas numbers

Name	CAS No
cannabigerol	25654-31-3, 26645-67-0

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.