

Novachem Pty Ltd

Version No: 1.1 Safety Data Sheet according to WHS and ADG requirements Chemwatch Hazard Alert Code: 4

Issue Date: **06/03/2018**Print Date: **06/03/2018**S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Clonazepam
Chemical Name	clonazepam
Synonyms	C-907
Proper shipping name	METHANOL
Chemical formula	C15-H10-CI-N3-O3
Other means of identification	Not Available
CAS number	1622-61-3*

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Laboratory chemicals, Manufacture of substances

Details of the supplier of the safety data sheet

Registered company name	Novachem Pty Ltd	
Address	25 Crissane Road, Heidelberg West Victoria 3081 Australia	
Telephone	+61384151255	
Fax	+61386250088	
Website	www.novachem.com.au	
Email	novachem@novachem.com.au	

Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre	
Emergency telephone numbers	13 11 26	
Other emergency telephone numbers	Not Available	

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule		
Classification ^[1]		
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)







SIGNAL WORD DANGER

Hazard statement(s)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.

H370 Causes damage to organs

Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P307+P311	IF exposed: Call a POISON CENTER or doctor/physician.
P330 Rinse mouth.	
P363	Wash contaminated clothing before reuse.

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

CAS No	%[weight]	Name
67-56-1	99.9	methanol
1622-61-3	0.1	donazepam

Mixtures

See section above for composition of Substances

SECTION 4 FIRST AID MEASURES

Description of first aid measures

If this product comes in contact with the eyes: ▶ Immediately hold eyelids apart and flush the eye continuously with running water. **Eve Contact** Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel If skin or hair contact occurs: • Quickly but gently, wipe material off skin with a dry, clean cloth. **Skin Contact** Immediately remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Inhalation Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay. IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. ► For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. ▶ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be

Ingestion

- provided. Further action will be the responsibility of the medical specialist.
- If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS.

Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed

▶ INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.

NOTE: Wear a protective glove when inducing vomiting by mechanical means.

▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Chemwatch: 9-517674 Page 3 of 9 Issue Date: 06/03/2018 Version No: 1.1 Print Date: 06/03/2018

Clonazepam

Indication of any immediate medical attention and special treatment needed

For anticonvulsants:

It is recommended that the physician withdraw the drug slowly on the appearance of unusual depression, aggressiveness, or other behavioral alterations.

As with other anticonvulsants, it is important to proceed slowly when increasing or decreasing dosage, as well as when adding or eliminating other medication. Abrupt withdrawal of anticonvulsant medication may precipitate absence (petit mal) status

For severe benzodiazepine overdose the stomach should be emptied by aspiration and lavage. Recovery usually follows symptomatic relief.

Dialysis is of no value. [Martindale]

For acute and short term repeated exposures to methanol:

- ► Toxicity results from accumulation of formaldehyde/formic acid.
- Figure 2 Clinical signs are usually limited to CNS, eyes and GI tract Severe metabolic acidosis may produce dyspnea and profound systemic effects which may become intractable. All symptomatic patients should have arterial pH measured. Evaluate airway, breathing and circulation.
- ▶ Stabilise obtunded patients by giving naloxone, glucose and thiamine.
- Decontaminate with Ipecac or lavage for patients presenting 2 hours post-ingestion. Charcoal does not absorb well; the usefulness of cathartic is not established.
- Forced diuresis is not effective; haemodialysis is recommended where peak methanol levels exceed 50 mg/dL (this correlates with serum bicarbonate levels below 18 meq/L).
- Ethanol, maintained at levels between 100 and 150 mg/dL, inhibits formation of toxic metabolites and may be indicated when peak methanol levels exceed 20 mg/dL. An intravenous solution of ethanol in D5W is optimal.
- Folate, as leucovorin, may increase the oxidative removal of formic acid. 4-methylpyrazole may be an effective adjunct in the treatment. 8. Phenytoin may be preferable to diazepam for controlling seizure.

[Ellenhorn Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

Determinant Index Sampling Time Comment 1 Methanol in urine 15 mg/l Fnd of shift B NS Before the shift at end of workweek B NS 2 Formic acid in urine 80 mg/gm creatinine

B: Background levels occur in specimens collected from subjects NOT exposed.

NS: Non-specific determinant - observed following exposure to other materials.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Water may be an ineffective extinguishing media for methanol fires; static explosions are reported for aqueous solutions as dilute as 30%. Water may be used to cool containers.

- Alcohol stable foam.
- Drv chemical powder.
- ▶ BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result	
Advice for firefighters	
Eire Eighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive.

	Fire Fighting	 Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course.
		Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers.
		 Vapour may travel a considerable distance to source of ignition.
	Fire/Explosion Hazard	Heating may cause expansion or decomposition leading to violent rupture of containers.
		Combustion products include:
		carbon dioxide (CO2)

formaldehyde

other pyrolysis products typical of burning organic material

•2WE

HAZCHEM

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus.

Issue Date: 06/03/2018 Print Date: 06/03/2018

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling

- ▶ Containers, even those that have been emptied, may contain explosive vapours.
- Do NOT cut, drill, grind, weld or perform similar operations on or near containers.
- Avoid all personal contact, including inhalation.
- ▶ Wear protective clothing when risk of exposure occurs.
- Use in a well-ventilated area.
- Prevent concentration in hollows and sumps

Other information

Suitable container

- ▶ Store in original containers in approved flame-proof area.
- ▶ No smoking, naked lights, heat or ignition sources
- ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped.
- Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

- ▶ Glass container is suitable for laboratory quantities
- Packing as supplied by manufacturer.
- Plastic containers may only be used if approved for flammable liquid.
 - Check that containers are clearly labelled and free from leaks
 - For low viscosity materials (i): Drums and jerry cans must be of the non-removable head type. (ii): Where a can is to be used as an inner package, the can must have a screwed enclosure.
 - For materials with a viscosity of at least 2680 cSt. (23 deg. C)
 - ▶ For manufactured product having a viscosity of at least 250 cSt.

- reacts violently with strong oxidisers, acetyl bromide, alkyl aluminium salts, beryllium dihydride, bromine, chromic acid, 1-chloro-3,3-difluoro-2-methoxycyclopropene, cyanuric chloride, diethylzinc, isophthaloyl chloride, nitric acid, perchloric acid, potassium-tert-butoxide, potassium sulfur diimide, Raney nickel catalysts, 2,4,6-trichlorotriazine, triethylaluminium, 1,3,3-trifluoro-2-methoxycyclopropene
- ▶ is incompatible with strong acids, strong caustics, alkaline earth and alkali metals, aliphatic amines, acetaldehyde, benzoyl peroxide, 1,3-bis(din-cyclopentadienyl iron)-2-propen-1-one, calcium carbide, chloroform, chromic anhydride, chromium trioxide, dialkylzinc, dichlorine oxide, dichloromethane, ethylene oxide, hypochlorous acid, isocyanates, isopropyl chlorocarbonate, lithium tetrahydroaluminate, magnesium, methyl azide, nitrogen dioxide, palladium, pentafluoroguanidine, perchloryl fluoride, phosphorus pentasulfide, phosphorus trioxide, potassium, tangerine oil, triisobutylaluminium
- ▶ mixtures with lead perchlorate, sodium hypochlorite are explosive
- may react with metallic aluminium at high temperatures
 - slowly corrodes lead and aluminium
 - may generate electrostatic charges, due to low conductivity, on flow or agitation
 - attacks some plastics, rubber and coatings.

Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content Alcohols

- are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.
- reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen
- react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium
- should not be heated above 49 deg. C. when in contact with aluminium equipment
- Avoid storage with reducing agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

Storage incompatibility

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	methanol	Methyl alcohol	262 mg/m3 / 200 ppm	328 mg/m3 / 250 ppm	Not Available	Not Available

EMERGENCY LIMITS

Ingredient	Material name TEEL-1			TEEL-2	TEEL-3		
methanol	Methyl alcohol; (Methanol) Not Available			Not Available	Not Available		
Ingredient	Original IDLH			Revised IDLH			
methanol	6000 ppm	Not Available					
clonazepam	Not Available	Not Availab	ble				

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment

Personal protection











Version No: 1.1

Issue Date: 06/03/2018 Print Date: 06/03/2018 Clonazepam

Eye and face protection	 Safety glasses with side shields Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.
Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

Clonazepam

Material	СРІ
BUTYL	A
BUTYL/NEOPRENE	A
PE/EVAL/PE	A
PVDC/PE/PVDC	A
SARANEX-23 2-PLY	A
SARANEX-23	A
TEFLON	A
VITON/NEOPRENE	A
NEOPRENE	В
NAT+NEOPR+NITRILE	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
PVA	С
PVC	С

^{*} CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

Respiratory protection

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	A-AUS / Class	-
		1	
up to 50	1000	-	A-AUS / Class
			1
up to 50	5000	Airline *	-
up to 100	5000	-	A-2
up to 100	10000	-	A-3
100+		-	Airline**

^{* -} Continuous Flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gases, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = $\frac{1}{2}$ Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 deg C)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

.			
Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	0.791 @ 20 C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available

^{*} Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

^{** -} Continuous-flow or positive pressure demand.

Issue Date: 06/03/2018 Print Date: 06/03/2018

	1		•
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	64-65	Molecular weight (g/mol)	Not Available
Flash point (°C)	9.7 CC	Taste	Not Available
Evaporation rate	2.1 BuAc=1 BuAC = 1	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	36	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	6	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Neutral
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

	*
Reactivity	See section 7
Chemical stability	 Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content. Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

TOXICITY

methanol

produce serious damage to the health of the individual. Benzodiazepine overdose is frequent, but serious poisonings are uncommon, sometimes even in high doses. The most common side-effects are drowsiness, dizziness and inco-ordination.	Information on toxicological	effects			
Ingestion Ingest	Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract follo using animal models). Nevertheless, adverse systemic effects have been produced following exposure of at hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used i Minor but regular methanol exposures may effect the central nervous system, optic nerves and retinae. Sym nausea, blurring of vision and double vision. Continued or severe exposures may cause damage to optic ner visual impairment even blindness resulting. WARNING: Methanol is only slowly eliminated from the body and should be regarded as a cumulative pois [CCINFO] Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal har	wing inhalation (as classified by EC Directives nimals by at least one other route and good in an occupational setting, ptoms may be delayed, with headache, fatigue, ves, which may become severe with permanent on which cannot be made non-harmful indling, may produce toxic effects.		
The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to use of the material and ensure that any external damage is suitably protected. There is strong evidence to suggest that this material, on a single contact with skin, can cause serious, irreversible damage of organs. Although the liquid is not thought to be an irritant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). 510meth Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Prolonged use of benzodiazepines can lead to alcoholism-like dependence. Tolerance and withdrawal symptoms are seen in long-term treatment in his doses. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision Liver and/or kidney injury may also result. TOXICITY IRRITATION	Ingestion	Benzodiazepine overdose is frequent, but serious poisonings are uncommon, sometimes even in high doses. The most common side-effects are drowsiness, dizziness and inco-ordination. Methanol may produce a burning or painful sensation in the mouth, throat, chest, and stomach. This may be accompanied by nausea, vomiting, headached dizziness, shortness of breath, weakness, fatigue, leg cramps, restlessness, confusion, drunken behaviour, visual disturbance, drowsiness, coma and			
characterised by tearing or conjunctival redness (as with windburn). 510meth Ample evidence from experiments exists that there is a suspicion this material directly reduces fertility. Prolonged use of benzodiazepines can lead to alcoholism-like dependence. Tolerance and withdrawal symptoms are seen in long-term treatment in his doses. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision Liver and/or kidney injury may also result. TOXICITY IRRITATION	Skin Contact	The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Tempolonged dermal exposures. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury was of the material and ensure that any external damage is suitably protected.	with harmful effects. Examine the skin prior to the		
Prolonged use of benzodiazepines can lead to alcoholism-like dependence. Tolerance and withdrawal symptoms are seen in long-term treatment in his doses. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision Liver and/or kidney injury may also result. TOXICITY IRRITATION	Еуе	characterised by tearing or conjunctival redness (as with windburn).	re may produce transient discomfort		
Clonazepam	Chronic	Prolonged use of benzodiazepines can lead to alcoholism-like dependence. Tolerance and withdrawal sym doses. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative of disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigonal control of the control of t	effects characterised by gastrointestinal		
Clonazepam					
Oral (rat) LD50: >15000 mg/kg ^[2] Not Available	Clonazepam		-		
		Oral (rat) LD50: >15000 mg/kg ^[2]	Not Available		

IRRITATION

Chemwatch: 9-517674 Page 7 of 9 Issue Date: 06/03/2018 Version No: 1.1 Print Date: 06/03/2018

Clonazepam

	Dermal (rabbit) LD50: 15800 mg/kg ^[2]	Eye (rabbit): 100 mg/2	24h-moderate
	Inhalation (rat) LC50: 63926.976 mg/l/4h ^[2]	Eye (rabbit): 40 mg-m	noderate
	Oral (rat) LD50: 5600 mg/kg ^[2]	Skin (rabbit): 20 mg/2	4 h-moderate
clonazepam	TOXICITY		IRRITATION
Cionazepani	Oral (rat) LD50: >15000 mg/kg ^[2]		Not Available
Legend:	 Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Valudata extracted from RTECS - Register of Toxic Effect of chemical Substances 	ue obtained from manu	facturer's SDS. Unless otherwise specified
	Ü		
METHANOL	The material may cause skin irritation after prolonged or repeated exposure and may scaling and thickening of the skin.	produce on contact sk	in redness, swelling, the production of vesicles,
CLONAZEPAM	Reports suggest an association between the use of anticonvulsant drugs by women we to these women. However, whether the abnormalities are caused by the maternal epile unsubstantiated by study till date. Exposure in utero has lead to high frequency of "antihypoplasia of the mid face and fingers. As such, pregnant patients with seizure disorce anticonvulsant therapy. Exposure to the material for prolonged periods may cause physical defects in the deversaciculation, effects on fertility, foetotoxicity, specific developmental abnormalities (correcorded.	epsy itself or by exposu iconvulsant embryopat ders should be carefull reloping embryo (terato	re to anticonvulsant drugs is unclear and hy" characterised by growth retardation, and y considered before administrating genesis).
Acute Toxicity	✓ Carcin	ogenicity	
Skin Irritation/Corrosion		oductivity	
Serious Eye Damage/Irritation	STOT - Single E	Exposure 🗸	
Respiratory or Skin sensitisation	STOT - Repeated E	Exposure 🛇	
Mutagenicity	○ Aspiratio	n Hazard 🛇	

Legend:

🗶 – Data available but does not fill the criteria for classification

✓ – Data available to make classification

O - Data Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Clonazonam	ENDPOINT		TEST DURATION (HR)		SPECIES	VALUE		SOUF	RCE
Cionazepani	Clonazepam Not Available		Not Available		Not Available	Not Avail	able	Not Available	
	ENDPOINT	TE	CCT DUD ATION (UD)	eproir			VALUE		SOURCI
			ST DURATION (HR)	SPECIE	:5				SOURCE
	LC50	96		Fish			>100mg/L		4
	EC50	48	48		Crustacea		>10000mg/L 4		4
methanol	EC50	96	96		Algae or other aquatic plants		<10000mg/L		4
	BCF	24		Algae o	Algae or other aquatic plants		0.05mg/L		4
	EC0	168		Algae o	Algae or other aquatic plants		=530mg/L		1
	NOEC	72		Crustac	ea		0.1mg/L		4
alanazanam	ENDPOINT		TEST DURATION (HR)		ST DURATION (HR) SPECIES			SOUF	RCE
clonazepam	Not Available	Not Available			Not Available Not Av		able	Not A	vailable

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For Methanol: Log Kow: -0.82 to -0.66; Koc: 1; Henry \odot s Law Constant: 4.55x10-6 atm-cu m/mole; Vapor Pressure: 127 mm Hg; BCF: <10.

Atmospheric Fate: Methanol is expected to exist solely as a vapor in the ambient atmosphere. Vapor-phase methanol is broken down in the atmosphere by reactions with hydroxyl radicals; the half-life for this reaction in air is estimated to be 17 days.

Terrestrial Fate: Methanol is expected to have very high mobility in soil.

DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
methanol	LOW	LOW
clonazepam	HIGH	HIGH

Issue Date: **06/03/2018** Print Date: **06/03/2018**

Clonazepam

Ingredient	Bioaccumulation
methanol	LOW (BCF = 10)
clonazepam	LOW (LogKOW = 2.41)

Mobility in soil

Ingredient	Mobility
methanol	HIGH (KOC = 1)
clonazepam	LOW (KOC = 10420)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

- ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
- Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
 - ▶ Reuse
 - Recycling
 - ► Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains
- It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ► Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- ► Decontaminate empty containers.

SECTION 14 TRANSPORT INFORMATION

Labels Required





Marine Pollutant

NO

HAZCHEM •2WE

Land transport (ADG)

UN number	1230			
UN proper shipping name	METHANOL			
Transport hazard class(es)	Class 3 Subrisk 6.1			
Packing group	II .			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions 279 Limited quantity 1 L			

Air transport (ICAO-IATA / DGR)

UN number	1230		
UN proper shipping name	Methanol		
	ICAO/IATA Class	3	
Transport hazard class(es)	ICAO / IATA Subrisk	6.1	
	ERG Code	3L	

Version No: 1.1

Issue Date: 06/03/2018 Print Date: 06/03/2018

Sea transport (IMDG-Code / GGVSee)

UN number	1230			
UN proper shipping name	METHANOL			
Transport hazard class(es)	IMDG Class 3 IMDG Subrisk 6.1			
Packing group	П			
Environmental hazard	Not Applicable			
Special precautions for user	EMS Number F-E, S-D Special provisions 279 Limited Quantities 1 L			

Clonazepam

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

METHANOL(67-56-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS Australia Exposure Standards Australia Inventory of Chemical Substances (AICS)

Australia Hazardous Substances Information System - Consolidated Lists

CLONAZEPAM(1622-61-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

National Inventory	Status		
Australia - AICS	Υ		
Canada - DSL	Y		
Canada - NDSL	N (methanol; clonazepam)		
China - IECSC	N (clonazepam)		
Europe - EINEC / ELINCS / NLP	Υ		
Japan - ENCS	N (clonazepam)		
Korea - KECI	N (clonazepam)		
New Zealand - NZIoC	Υ		
Philippines - PICCS	N (clonazepam)		
USA - TSCA	N (clonazepam)		
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)		

SECTION 16 OTHER INFORMATION

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.