

Novachem Pty Ltd

Version No: 2.2

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: **17/03/2023** Print Date: **17/03/2023** S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Furanic Compound Calibration Standard
Synonyms	Not Available
Proper shipping name	TOLUENE
Other means of identification	D-5837-02

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Laboratory Chemical Reference Material

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Novachem Pty Ltd	Novachem Pty Ltd
Address	25 Crissane Road, Heidelberg West Victoria 3081 Australia	25 Crissane Road, Heidelberg West Victoria 3081 Australia
Telephone	+61384151255	+61384151255
Fax	+61386250088	+61386250088
Website	www.novachem.com.au	www.novachem.com.au
Email	novachem@novachem.com.au	novachem@novachem.com.au

Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre	Victorian Poisons Information Centre
Emergency telephone numbers	13 11 26	13 11 26
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 Hazards identification

Poisons Schedule	Not Applicable
Classification ^[1]	Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Reproductive Toxicity Category 1A, Specific Target Organ Toxicity - Repeated Exposure Category 2, Flammable Liquids Category 2, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 2, Aspiration Hazard Category 1, Carcinogenicity Category 2
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

Label elements

Hazard pictogram(s)	
Signal word	Danger

Hazard statement(s)

H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H360	May damage fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure.

H225	Highly flammable liquid and vapour.
H335	May cause respiratory irritation.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H304	May be fatal if swallowed and enters airways.
H351	Suspected of causing cancer.

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P271	Use only a well-ventilated area.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.	
P331	Do NOT induce vomiting.	
P308+P313	IF exposed or concerned: Get medical advice/ attention.	
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.	

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures


Mixtures

CAS No	%[weight]	Name
1192-62-7	0.1	2-acetylfuran
98-00-0	0.1	furfuryl alcohol
67-47-0	0.1	5-(hydroxymethyl)furfural
98-01-1	0.1	furfural
620-02-0	0.1	5-methylfurfural
108-88-3	99.5	toluene
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures

Eye Contact	 If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin contact occurs: Immediately remove all contaminated clothing, including footwear. Flush skin and hair with running water (and soap if available). Seek medical attention in event of irritation.
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.



Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours. Following acute or short term repeated exposures to toluene:

- Toluene is absorbed across the alveolar barrier, the blood/air mixture being 11.2/15.6 (at 37 degrees C.) The concentration of toluene, in expired breath, is of the order of 18 ppm following sustained exposure to 100 ppm. The tissue/blood proportion is 1/3 except in adipose where the proportion is 8/10.
- Metabolism by microsomal mono-oxygenation, results in the production of hippuric acid. This may be detected in the urine in amounts between 0.5 and 2.5 g/24 hr which represents, on average 0.8 gm/gm of creatinine. The biological half-life of hippuric acid is in the order of 1-2 hours.
- Primary threat to life from ingestion and/or inhalation is respiratory failure.
- Patients should be quickly evaluated for signs of respiratory distress (eg cyanosis, tachypnoea, intercostal retraction, obtundation) and given oxygen. Patients with inadequate tidal volumes or poor arterial blood gases (pO2 <50 mm Hg or pCO2 > 50 mm Hg) should be intubated.
- Arrhythmias complicate some hydrocarbon ingestion and/or inhalation and electrocardiographic evidence of myocardial damage has been reported; intravenous lines and cardiac monitors should be established in obviously symptomatic patients. The lungs excrete inhaled solvents, so that hyperventilation improves clearance.
- A chest x-ray should be taken immediately after stabilisation of breathing and circulation to document aspiration and detect the presence of pneumothorax.
- Epinephrine (adrenaline) is not recommended for treatment of bronchospasm because of potential myocardial sensitisation to catecholamines. Inhaled cardioselective bronchodilators (e.g. Alupent, Salbutamol) are the preferred agents, with aminophylline a second choice.
- Lavage is indicated in patients who require decontamination; ensure use.

BIOLOGICAL EXPOSURE INDEX - BEI

These represent the determinants observed in specimens collected from a healthy worker exposed at the Exposure Standard (ES or TLV):

Determinant	Index	Sampling Time	Comments
o-Cresol in urine	0.5 mg/L	End of shift	В
Hippuric acid in urine	1.6 g/g creatinine	End of shift	B, NS
Toluene in blood	0.05 mg/L	Prior to last shift of workweek	

NS: Non-specific determinant; also observed after exposure to other material

B: Background levels occur in specimens collected from subjects NOT exposed

SECTION 5 Firefighting measures

Extinguishing media

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
----------------------	--

Advice for firefighters

Fire Fighting	
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. Combustion products include: carbon dioxide (CO2) other pyrolysis products typical of burning organic material. Contains low boiling substance: Closed containers may rupture due to pressure buildup under fire conditions.
HAZCHEM	3YE

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves. Prevent, by any means available, spillage from entering drains or water course.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling	
Safe handling	 Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Contains low boiling substance: Storage in sealed containers may result in pressure buildup causing violent rupture of containers not rated appropriately. Check for bulging containers. Vent periodically Always release caps or seals slowly to ensure slow dissipation of vapours Electrostatic discharge may be generated during pumping - this may result in fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment. Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<=1 m/sec until fill pipe submerged to twice its diameter, then <= 7 m/sec). Avoid splash filling. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. DO NOT allow clothing wet with material to stay in contact with skin
Other information	 Storage of furfural (syn: 2-furaldehyde) in air for extended periods is not recommended because polymer formation, darkening of colour and increases in acidity can occur. Storage under an inert gas such as nitrogen is recommended. Violent polymerisation can occur upon contact with strong mineral acids, alkalis or at elevated temperatures. Store in original containers in approved flame-proof area. No smoking, naked lights, heat or ignition sources. DO NOT store in pits, depression, basement or areas where vapours may be trapped. Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	 Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks. For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) For manufactured product having a viscosity of at least 250 cSt.
Storage incompatibility	 For furfural: Strong acids or bases may cause polymerisation. Reacts violently with strong acids, alkalis, sodium bicarbonate. Incompatible with ammonia, aliphatic amines, alkanolamines. aromatic amines. Toluene: reacts violently with strong oxidisers, bromine, bromine trifluoride, chlorine, hydrochloric acid/ sulfuric acid mixture, 1,3-dichloro-5,5-dimethyl-2,4-imidazolidindione, dinitrogen tetraoxide, fluorine, concentrated nitric acid, nitrogen dioxide, silver chloride, sulfur dichloride, uranium fluoride, vinyl acetate forms explosive mixtures with strong acids, strong oxidisers, silver perchlorate, tetranitromethane is incompatible with bis-toluenediazo oxide attacks some plastics, rubber and coatings may generate electrostatic charges, due to low conductivity, on flow or agitation. For alkyl aromatics: The alkyl side chain of aromatic rings can undergo oxidation by several mechanisms. The most common and dominant one is the attack by oxidation product formed (provided a hydrogen atom is initially available at this position) - this product is often short-lived but may be stable dependent on the nature of the aromatic substitution; a secondary C-H bond is more easily attacked than a primary C-H bond whilst a tertiary C-H bond is even more susceptible to attack by oxygen Monoalkylbenzenes may subsequently form monocarboxylic acids; alkyl naphthalenes mainly produce the corresponding naphthalene carboxylic acids. Oxidation in the presence of transition metal salts not only accelerates but also selectively decomposes the hydroperoxides. Vigorous reactions, sometimes amounting to explosions, can result from the contact between aromatic rings and strong oxidising agents. Aromatics can react exothermically with bases and with diazo compounds.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	furfuryl alcohol	Furfuryl alcohol	10 ppm / 40 mg/m3	60 mg/m3 / 15 ppm	Not Available	Not Available
Australia Exposure Standards	furfural	Furfural	2 ppm / 7.9 mg/m3	Not Available	Not Available	Not Available
Australia Exposure Standards	toluene	Toluene	50 ppm / 191 mg/m3	574 mg/m3 / 150 ppm	Not Available	Not Available

Emergency Limits

Ingredient	TEEL-1	TEEL-2	TEEL-3
furfuryl alcohol	15 ppm	42 ppm	250 ppm

Ingredient	TEEL-1	TEEL-2		TEEL-3	
furfural	Not Available	Not Available		Not Available	
toluene	Not Available	Not Available		Not Available	
Ingredient	Original IDLH		Revised IDLH		
2-acetylfuran	Not Available		Not Available		
furfuryl alcohol	75 ppm		Not Available		
5-(hydroxymethyl)furfural	Not Available		Not Available		
furfural	100 ppm		Not Available		
5-methylfurfural	Not Available		Not Available		
toluene	500 ppm		Not Available		
Occupational Exposure Banding					
Ingredient	Occupational Exposure Band Rating		Occupational Ex	Occupational Exposure Band Limit	
2-acetylfuran	E	E		≤ 0.01 mg/m³	
5-(hydroxymethyl)furfural	E		≤ 0.01 mg/m³	≤ 0.01 mg/m³	
5-methylfurfural	E		≤ 0.1 ppm		
Notes:	adverse health outcomes associate		process is an occupation	r bands based on a chemical's potency and the onal exposure band (OEB), which corresponds to	
xposure controls	·				
Appropriate engineering controls	be highly effective in protecting wo The basic types of engineering con Process controls which involve cha	rkers and will typically be independe ntrols are: anging the way a job activity or proce sion source which keeps a selected h	nt of worker interaction	the hazard. Well-designed engineering controls ca is to provide this high level of protection. he risk. ay from the worker and ventilation that strategically	
Individual protection measures, such as personal protective equipment					

Eye and face protection
 Safety glasses with side shields.
 Chemical goggles.
 Contact large may pose a spec

Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Furanic Compound Calibration Standard

Material	CPI
PE/EVAL/PE	А
PVA	А
BUTYL	С
BUTYL/NEOPRENE	С

Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	A-AUS	-	A-PAPR-AUS / Class 1
up to 50 x ES	-	A-AUS / Class 1	-

CPE	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
NITRILE+PVC	С
PVC	С
SARANEX-23	С
SARANEX-23 2-PLY	С
TEFLON	С
VITON	С
VITON/CHLOROBUTYL	С
VITON/NEOPRENE	С

up to 100 x ES - A-2 A-PAPR-2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

SECTION 9 Physical and chemical properties

selection must be based on detailed observation.

* CPI - Chemwatch Performance Index

A: Best Selection

should be consulted.

Information on basic physical and chemical properties

B: Satisfactory; may degrade after 4 hours continuous immersion C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner

Appearance	Clear liquid		
Physical state	Liquid	Relative density (Water = 1)	0.866
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	-93	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	110.6	Molecular weight (g/mol)	Not Available
Flash point (°C)	4	Taste	Not Available
Evaporation rate	2.2 BuAC = 1	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available
Upper Explosive Limit (%)	7.1	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	1.3	Volatile Component (%vol)	>99
Vapour pressure (kPa)	2.92	Gas group	Not Available
Solubility in water	Immiscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	3.2	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7

 Incompatible materials
 See section 7

 Hazardous decomposition products
 See section 5

SECTION 11 Toxicological information

formation on toxicological e	ifects			
Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack or co-ordination, and vertigo. Furfural vapours irritate the nose and throat. Low levels cause headache, throat itching and eye irritation. High concentrations may cause nausea, vomiting, unconsciousness and death. Other effects for inhaling furfural are as for swallowing. Inhalation of high concentrations of gas/vapour causes lung irritation with coughing and nausea, central nervous depression with headache and dizziness, slowing of reflexes, fatigue and inco-ordination. Central nervous system (CNS) depression may include general discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression are may be fatal. The acute toxicity of inhaled alkylbenzene is best described by central nervous system depression. These compounds may also act as general anaesthetics. Whole body symptoms of poisoning include light-headedness, nervousness, apprehension, a feeling of well-being, confusion, dizziness, drowsiness, inging in the ears, blurred or double vision, vomiting and sensations of heat, cold or numbness, twitching, tremors, convulsions, unconsciousness, depression of breathing, and arrest. Heart stoppage may result from cardiovascular collapse. The use of a quantity of material in an unventilated or confined space may result in increased exposure and an irritating atmosphere developing Before starting consider control of exposure by mechanical ventilation.			
Ingestion	Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practic requires that exposure be kept to a minimum. Swallowing furfural (2-furaldehyde) may cause numbness of the tongue and mucous membranes of the mouth, loss of taste sense, difficulty in breathing, nausea, vomiting and severe headache. As little as 0.06 gram, if swallowed or otherwise absorbed, will cause severe headache. At sufficiently high doses the material may be hepatotoxic (i.e. poisonous to the liver). Considered an unlikely route of entry in commercial/industrial environments. The liquid may produce gastrointestinal discomfort and may be harmful if swallowed.			
Skin Contact	The material may accentuate any pre-existing dermatitis condition Skin contact with the material may damage the health of the individual; systemic effects may result following absorption. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.			
Eye	The liquid produces a high level of eye discomfort and is capable of causing pain and severe conjunctivitis. Corneal injury may develop, with possible permanent impairment of vision, if not promptly and adequately treated. There is evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Severe inflammation may be expected with pain.			
Chronic	Long-term exposure to respiratory irritants may result in air Toxic: danger of serious damage to health by prolonged ex This material can cause serious damage if one is exposed produce severe defects. Ample evidence exists that this material directly causes rec Ample evidence exists that developmental disorders are dii Substance accumulation, in the human body, may occur an Chronic effects of furfural include eczema, allergic sensitisz Repeated or prolonged skin contact may stain the skin yelle Intentional abuse (glue sniffing) or occupational exposure to tremors of the extremeties (due to widespread cerebrum wi	rectly caused by human exposure to the material. In may cause some concern following repeated or long-term occupational exposure.		
Furanic Compound	τοχιςιτγ	IRRITATION		
Calibration Standard	Not Available	Not Available		
Calibration Standard				
	тохісіту	IRRITATION		
2-acetylfuran	TOXICITY Inhalation(Rat) LC50: 1.13 mg/L4h ^[2]	IRRITATION Not Available		
2-acetylfuran	Inhalation(Rat) LC50: 1.13 mg/L4h ^[2]	Not Available		
	Inhalation(Rat) LC50: 1.13 mg/L4h ^[2]	Not Available IRRITATION		
2-acetylfuran	Inhalation(Rat) LC50: 1.13 mg/L4h ^[2] TOXICITY Dermal (rabbit) LD50: 400 mg/kg ^[2]	Not Available IRRITATION		
2-acetylfuran	Inhalation(Rat) LC50: 1.13 mg/L4h ^[2] TOXICITY Dermal (rabbit) LD50: 400 mg/kg ^[2] Inhalation(Rat) LC50: >0.82<2.07 mg/L4h ^[1]	Not Available IRRITATION		

	ΤΟΧΙCΙΤΥ	IRRITATION	
	dermal (rat) LD50: 192.39 mg/kg ^[1]	Eye (rabbit): 100 mg/24h moderate	
furfural	Inhalation(Rat) LC50: >0.54<1.63 mg/l4h ^[1]	Eye: adverse effect observed (irritating) ^[1]	
	Oral (Rat) LD50: 65 mg/kg ^[2]	Skin (rabbit): 20 mg/24h moderate	
		Skin: adverse effect observed (irritating) ^[1]	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
5-methylfurfural	Oral (Rat) LD50: 2200 mg/kg ^[2]	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: 12124 mg/kg ^[2]	Eye (rabbit): 2mg/24h - SEVERE	
	Inhalation(Rat) LC50: >13350 ppm4h ^[2]	Eye (rabbit):0.87 mg - mild	
	Oral (Rat) LD50: 636 mg/kg ^[2]	Eye (rabbit):100 mg/30sec - mild	
toluene		Eye: adverse effect observed (irritating) ^[1]	
		Skin (rabbit):20 mg/24h-moderate	
		Skin (rabbit):500 mg - moderate	
		Skin: adverse effect observed (irritating) ^[1]	
		Skin: no adverse effect observed (not irritating) ^[1]	
Legend:	1. Value obtained from Europe ECHA Registered Substance specified data extracted from RTECS - Register of Toxic Effi	es - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise ect of chemical Substances	
· ·			
Furanic Compound Calibration Standard	cessation of exposure, the level of aromatic hydrocarbon	tic hydrocarbons undergo substantial partitioning into adipose tissues. Following s in body fats rapidly declines. Thus, the aromatic hydrocarbons are unlikely to romatic hydrocarbons into the non-adipose tissues is unlikely.	
	Substance has been investigated as a tumorigen: and as a mutagen		

	bloaccumulate in the body. Selective partitioning	of the aromatic hydrocarbons into the r	ion-adipose tissues is unlikely.
	Substance has been investigated as a tumoriger Animal experiments indicate that liquid furfuryl a		, with deaths related to dose.
FURFURYL ALCOHOI	For furfuryl alcohol, furfural and furfuryl esters: Animal testing shows that these substances can	damage the liver. It is mostly excreted i	n the urine.
	The material may produce moderate eye irritatio conjunctivitis.	n leading to inflammation. Repeated or	prolonged exposure to irritants may produce
5-(HYDROXYMETHYL)FURFURAL	Equivocal tumorigen by RTECS criteria.		
FURFURAI	Carcinogenic by RTECS criteria (oral mouse live in lymphocytes observed at 70 micromol/litre 55		ated as a mutagen; Human sister chromatid exchange
Furanic Compound Calibration Standard & 2-ACETYLFURAN & FURFURYL ALCOHOL & 5-(HYDROXYMETHYL)FURFURAI & FURFURAL & 5-METHYLFURFURAI	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.		
Furanic Compound Calibration Standard & TOLUEN	For toluene: Acute toxicity: Humans exposed to high levels of toluene for short periods of time experience adverse central nervous system effects ranging from headaches to intoxication, convulsions, narcosis (sleepiness) and death. When inhaled or swallowed, toluene can cause severe central nervous system depression, and in large doses has a narcotic effect. 60mL has caused death. Death of heart muscle fibres, liver swelling, congestion and bleeding of the lungs and kidney injury were all found on autopsy. Exposure to inhalation at a concentration of 600 parts per million for 8 hours resulted in the same and more serious symptoms including euphoria (a feeling of well-being), dilated pupils, convulsions and nausea.		
2-ACETYLFURAN 8 5-(HYDROXYMETHYL)FURFURAI	The Joint FAO/WHO Expert Committee on Food Additives (the JECFA) reviewed a group of 40 furan-substituted aliphatic hydrocarbons, alcohols, aldehydes, ketones, carboxylic acids and related esters, sulfides, disulfides and ethers. The main concern with this group arises primarily from the carcinogenicity of furan itself, which is believed to involve a reactive genotoxic metabolite formed by epoxidation and opening of the furan ring. Furan is not a member of this group of flavouring agents, but all the members of the group contain a furan ring with either one or two substituents of varying complexity. In some flavouring agents, a substituent is present on one side of the furan ring only, whereas in others, substituents are present on both sides. No significant acute toxicological data identified in literature search.		
FURFURAL & TOLUEN	The material may cause skin irritation after prolo production of vesicles, scaling and thickening of		oduce on contact skin redness, swelling, the
Acute Toxicity	×	Carcinogenicity	¥
01.1.1.1.1.1.1.10	×	Reproductivity	✓
Skin Irritation/Corrosion	•	Reproductivity	•
Skin Irritation/Corrosion Serious Eye Damage/Irritation	* *	STOT - Single Exposure	* *
	*	. ,	*

Legend: X – Data either not available or does not fill the criteria for classification - Data available to make classification

SECTION 12 Ecological information

Europia Compound	Endpoint	Test Duration (hr)		Species		Value	Source
Furanic Compound Calibration Standard	Not Available	Not Available		Not Available		Not Available	Not Availabl
	Endpoint	Test Duration (hr)		Species		Value	Source
2-acetylfuran	Not Available	Not Available		Not Available		Not Available	Not Availabl
	Endpoint	Test Duration (hr)		Species		Value	Sourc
	EC0(ECx)	24h		Crustacea		6324mg/l	1
furfuryl alcohol	EC50	96h		Algae or other aquatic plants		170.278mg/l	2
	LC50	96h	1	Fish		361.959mg/l	2
	Endpoint	Test Duration (hr)		Species		Value	Sourc
5-(hydroxymethyl)furfural	NOEC(ECx)	72h		Algae or other aquatic plants		10.6mg/l	2
	EC50	72h		Algae or other aquatic plants		45.5mg/l	2
	EC50	48h		Crustacea 46.5mg/l		2	
	Endpoint	Test Duration (hr)	Sp	Species Value		ue	Sourc
	EC0(ECx)	24h	Cr	ustacea	132	24mg/l	1
furfural	EC50	96h	Alç	ae or other aquatic plants	11.	1mg/l	2
	LC50	96h	Fis	h	2.4	82-5.255mg/L	4
	EC50	48h	Cr	ustacea	>10)<56mg/l	4
	Endpoint	Test Duration (hr)		Species		Value	Source
5-methylfurfural	Not Available	Not Available		Not Available		Not Available	Not Availabl
	Endpoint	Test Duration (hr)		Species		Value	Sourc
	LC50	96h		Fish		5-35mg/l	4
	EC50	72h		Algae or other aquatic plants		12.5mg/l	4
toluene	EC50	48h		Crustacea		3.78mg/L	5
	NOEC(ECx)	168h		Crustacea		0.74mg/L	5
	EC50	96h		Algae or other aquatic plants		>376.71mg/L	4
		1	1	Substances - Ecotoxicological Inform			1

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

Environmental Fate: Furfural rapidly degrades in four sandy loam soils with 2-furoic acid as the major by-product. Furfural residues are highly mobile in three sandy loams but have low mobility in Bog sand.

Ecotoxicity: Avian acute oral toxicity: Furfural is found to be moderately toxic to Mallard ducks and Japanese quail.

Acute fish toxicity: Toxicity test conducted on Bluegill sunfish and rainbow trout show that furfural is moderately toxic to fish.

For Aromatic Substances Series:

Environmental Fate: Large, molecularly complex polycyclic aromatic hydrocarbons, or PAHs, are persistent in the environment longer than smaller PAHs.

Atmospheric Fate: PAHs are 'semi-volatile substances' which can move between the atmosphere and the Earth's surface in repeated, temperature-driven cycles of deposition and volatilization. Terrestrial Fate: BTEX compounds have the potential to move through soil and contaminate ground water, and their vapors are highly flammable and explosive. Ecotoxicity - Within an aromatic series, acute toxicity increases with increasing alkyl substitution on the aromatic nucleus.

For Toluene: log Kow : 2.1-3; log Koc : 1.12-2.85; Koc : 37-260; log Kom : 1.39-2.89; Half-life (hr) air : 2.4-104; Half-life (hr) H2O surface water : 5.55-528; Half-life (hr) H2O ground : 168-2628; Half-life (hr) soil : <48-240; Henry's Pa m3 /mol : 518-694; Henry's Patm 37/mol : 5.94; E-03BOD 5 0.86-2.12, 5%COD - 0.7-2.52,21-27%; ThOD - 3.13; BCF - 1.67-380; log BCF - 0.22-3.28. Atmospheric Fate: The majority of toluene evapora photochemically produced bydroxyl radicals. The e

Atmospheric Fate: The majority of toluene evaporates to the atmosphere from the water and soil. The main degradation pathway for toluene in the atmosphere is reaction with photochemically produced hydroxyl radicals. The estimated atmospheric half life for toluene is about 13 hours. **DO NOT** discharge into sewer or waterways.

Ingredient	Persistence: Water/Soil	Persistence: Air
2-acetylfuran	LOW	LOW
furfuryl alcohol	LOW	LOW
5-(hydroxymethyl)furfural	LOW	LOW
furfural	LOW	LOW
toluene	LOW (Half-life = 28 days)	LOW (Half-life = 4.33 days)

Bioaccumulative potential

Ingredient	Bioaccumulation
2-acetylfuran	LOW (LogKOW = 0.52)
furfuryl alcohol	LOW (LogKOW = 0.28)
5-(hydroxymethyl)furfural	LOW (LogKOW = -0.0853)
furfural	LOW (LogKOW = 0.41)
toluene	LOW (BCF = 90)

Mobility in soil

Ingredient	Mobility
2-acetylfuran	LOW (KOC = 25.05)
furfuryl alcohol	LOW (KOC = 8.492)
5-(hydroxymethyl)furfural	HIGH (KOC = 1.677)
furfural	LOW (KOC = 17.71)
toluene	LOW (KOC = 268)

SECTION 13 Disposal considerations

Waste treatment methods

	Containers may still present a chemical hazard/ danger when empty.
	Return to supplier for reuse/ recycling if possible.
	Otherwise:
	If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
	Where possible retain label warnings and SDS and observe all notices pertaining to the product.
	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in the area. In some areas, certain wastes must be tracked.
	A Hierarchy of Controls seems to be common - the user should investigate:
	▶ Reduction
	▶ Reuse
	▶ Recycling
Product / Packaging disposal	 Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
	DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	Recycle wherever possible.
	 Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
	 Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
	 Decontaminate empty containers.

SECTION 14 Transport information

Subsidiary risk

Not Applicable

Labels Required			
Marine Pollutant	NO		
HAZCHEM	3YE		
Land transport (ADG)			
UN number or ID number	1294		
UN proper shipping name	TOLUENE		
Transport hazard class(es)	Class	3 Nat Appliable	

Packing group	Ш	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions	Not Applicable

Air transport (ICAO-IATA / DGR)

UN number	1294			
UN proper shipping name	Toluene			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	3 Not Applicable 3L		
Packing group	11			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions		Not Applicable	
	Cargo Only Packing Instructions		364	
	Cargo Only Maximum Qty / Pack		60 L	
	Passenger and Cargo Packing Instructions		353	
	Passenger and Cargo Maximum Qty / Pack		5 L	
	Passenger and Cargo Limited Quantity Packing Instructions		Y341	
	Passenger and Cargo Limited Maximum Qty / Pack		1 L	

Sea transport (IMDG-Code / GGVSee)

UN number	1294			
UN proper shipping name	TOLUENE	TOLUENE		
Transport hazard class(es)		3 Not Applicable		
Packing group	П			
Environmental hazard	Not Applicable			
Special precautions for user	EMS Number Special provisions Limited Quantities		-	

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
2-acetylfuran	Not Available
furfuryl alcohol	Not Available
5-(hydroxymethyl)furfural	Not Available
furfural	Not Available
5-methylfurfural	Not Available
toluene	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
2-acetylfuran	Not Available
furfuryl alcohol	Not Available
5-(hydroxymethyl)furfural	Not Available
furfural	Not Available
5-methylfurfural	Not Available
toluene	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

Australian Inventory of Industrial Chemicals (AIIC)	Chemical Footprint Project - Chemicals of High Concern List
furfuryl alcohol is found on the following regulatory lists	
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Chemical Footprint Project - Chemicals of High Concern List
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
Australian Inventory of Industrial Chemicals (AIIC)	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2B: Possibly carcinogenic to humans
5-(hydroxymethyl)furfural is found on the following regulatory lists	
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	Australian Inventory of Industrial Chemicals (AIIC)
furfural is found on the following regulatory lists	
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic
5-methylfurfural is found on the following regulatory lists	
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6	Australian Inventory of Industrial Chemicals (AIIC)
toluene is found on the following regulatory lists	
Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals	Australian Inventory of Industrial Chemicals (AIIC)
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5	Chemical Footprint Project - Chemicals of High Concern List International Agency for Research on Cancer (IARC) - Agents Classified by the IARC
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -	Monographs - Not Classified as Carcinogenic

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -Schedule 6

National Inventory Status

National Inventory	Status	
Australia - AIIC / Australia Non-Industrial Use	Yes	
Canada - DSL	Yes	
Canada - NDSL	No (2-acetylfuran; furfuryl alcohol; 5-(hydroxymethyl)furfural; furfural; 5-methylfurfural; toluene)	
China - IECSC	Yes	
Europe - EINEC / ELINCS / NLP	Yes	
Japan - ENCS	No (5-(hydroxymethyl)furfural)	
Korea - KECI	Yes	
New Zealand - NZIoC	Yes	
Philippines - PICCS	Yes	
USA - TSCA	Yes	
Taiwan - TCSI	Yes	
Mexico - INSQ	No (5-(hydroxymethyl)furfural)	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	17/03/2023
Initial Date	17/03/2023

SDS Version Summary

Version	Date of Update	Sections Updated
1.2	17/03/2023	Toxicological information - Acute Health (eye), Toxicological information - Acute Health (inhaled), Toxicological information - Acute Health (skin), Toxicological information - Acute Health (swallowed), First Aid measures - Advice to Doctor, Toxicological information - Chronic Health, Hazards identification - Classification, Disposal considerations - Disposal, Exposure controls / personal protection - Engineering Control, Ecological Information - Environmental, Exposure controls / personal protection - Exposure Standard, Firefighting measures - Fire Fighter (extinguishing media), Firefighting measures - Fire Fighter (fire/explosion hazard), Firefighting measures - Fire Fighter (fire fighting), First Aid (skin), First Aid measures - Fire K Aid (swallowed), Handling and storage - Handling Procedure, Composition / information on ingredients. Stability and reactivity - Instability Condition, Exposure controls / personal protection - Personal Protection (ther), Exposure controls / personal protection - Personal Protection (ther), Accidental release measures - Spills (major), Accidental release measures - Spills (major), Accidental release measures - Spills (major), Accidental release requirement), Handling and storage - Storage (suitable container), Transport information - Transport, Transport Information, Name

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

end of SDS

Furanic Compound Calibration Standard

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors **BEI: Biological Exposure Index** AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.