

Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS)

Novachem Pty Ltd

Version No: **2.2**Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 2

Issue Date: **12/09/2018**Print Date: **12/09/2018**S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS)	
Chemical Name	3-(trimethylsilyl)-1-propanesulfonic acid, sodium	
Synonyms	DLM-32	
Chemical formula	C6-H16-O3-S-Si .Na	
Other means of identification	Not Available	
CAS number	2039-96-5*	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

Details of the supplier of the safety data sheet

Registered company name	Novachem Pty Ltd	
Address	25 Crissane Road, Heidelberg West Victoria 3081 Australia	
Telephone	+61384151255	
Fax	+61386250088	
Website	www.novachem.com.au	
Email	novachem@novachem.com.au	
	•	

Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre
Emergency telephone numbers	13 11 26
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	Not Applicable	
Classification [1]	Skin Corrosion/Irritation Category 2, Eye Irritation Category 2A, Specific target organ toxicity - single exposure Category 3 (respiratory tract irritation)	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)



SIGNAL WORD WARNING

Hazard statement(s)

H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.

Chemwatch: **9-491932** Page **2** of **7**

Version No: 2.2

Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS)

Issue Date: 12/09/2018 Print Date: 12/09/2018

P271	Use only outdoors or in a well-ventilated area.
P261	Avoid breathing dust/fumes.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P362 Take off contaminated clothing and wash before reuse.	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312	Call a POISON CENTER or doctor/physician if you feel unwell.
P337+P313	If eye irritation persists: Get medical advice/attention.

Precautionary statement(s) Storage

recautionary statement(s) storage	
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.

Precautionary statement(s) Disposal

P501 Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

CAS No	%[weight]	Name
2039-96-5	>98	3-(trimethylsilyl)-1-propanesulfonic acid, sodium

Mixtures

See section above for composition of Substances

SECTION 4 FIRST AID MEASURES

Description of first aid measures

If this product comes in contact with the eyes: Wash out immediately with fresh running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the Seek medical attention without delay; if pain persists or recurs seek medical attention. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If skin contact occurs: Immediately remove all contaminated clothing, including footwear. In lumber in this product comes in contact with the eyes: If this product comes in contact with fresh running water (and soap if available). Seek medical attention in event of irritation.	
Ingestion	 Immediately give a glass of water. First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

- ▶ Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).

Special hazards arising from the substrate or mixture

Fire Incompatibility

Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

Advice for firefighters

Alert Fire Brigade and tell them location and nature of hazard.
 Wear breathing apparatus plus protective gloves.

Fire Fighting

- Prevent, by any means available, spillage from entering drains or water courses.
- Prevent, by any means available, spillage from entering drains of water of
 Use water delivered as a fine spray to control fire and cool adjacent area.

Chemwatch: 9-491932 Page 3 of 7 Issue Date: 12/09/2018 Version No: 2.2 Print Date: 12/09/2018

Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS)

▶ Combustible solid which burns but propagates flame with difficulty; it is estimated that most organic dusts are combustible (circa 70%) - according to the circumstances under which the combustion process occurs, such materials may cause fires and / or dust explosions. ▶ Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions). Avoid generating dust, particularly clouds of dust in a confined or unventilated space as dusts may form an explosive mixture with air, and any source of ignition, i.e. flame or spark, will cause fire or explosion. Dust clouds generated by the fine grinding of the solid are a particular hazard; accumulations of fine dust (420 micron or less) may burn rapidly and fiercely if ignited - particles exceeding this limit will generally not form flammable dust clouds; once initiated, however, larger particles up to 1400 microns diameter will contribute to the propagation of an explosion. Fire/Explosion Hazard Combustion products include: carbon monoxide (CO) carbon dioxide (CO2) sulfur oxides (SOx) silicon dioxide (SiO2) other pyrolysis products typical of burning organic material. May emit poisonous fumes May emit corrosive fumes. HAZCHEM Not Applicable

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

monitoria in a contra in a con	
Minor Spills	 Clean up all spills immediately. Avoid breathing dust and contact with skin and eyes. Wear protective clothing, gloves, safety glasses and dust respirator. Use dry clean up procedures and avoid generating dust.
Major Spills	Moderate hazard. CAUTION: Advise personnel in area. Alert Emergency Services and tell them location and nature of hazard. Control personal contact by wearing protective clothing.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling	3
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. Organic powders when finely divided over a range of concentrations regardless of particulate size or shape and suspended in air or some other oxidizing medium may form explosive dust-air mixtures and result in a fire or dust explosion (including secondary explosions) Minimise airborne dust and eliminate all ignition sources. Keep away from heat, hot surfaces, sparks, and flame. Establish good housekeeping practices. Remove dust accumulations on a regular basis by vacuuming or gentle sweeping to avoid creating dust clouds.
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry area protected from environmental extremes. Store away from incompatible materials and foodstuff containers.

Conditions for safe storage, including any incompatibilities

- '	
Suitable container	 Polyethylene or polypropylene container. Check all containers are clearly labelled and free from leaks.
Storage incompatibility	► Avoid reaction with oxidising agents

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Sodium 2,2-dimethyl- 2-silapentane-5-sulfonate (DSS)	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	

Version No: 2.2

Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS)

Issue Date: 12/09/2018 Print Date: 12/09/2018

3-(trimethylsilyl)-1propanesulfonic acid, sodium

Not Available

Not Available

Exposure controls

Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

Personal protection











Eye and face protection

- Safety glasses with side shields
- Chemical goggles.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.

Skin protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final

Hands/feet protection

Personal hygiene is a key element of effective hand care.

Experience indicates that the following polymers are suitable as glove materials for protection against undissolved, dry solids, where abrasive particles are not present.

- ► polychloroprene.
- ▶ nitrile rubber
- butyl rubber.

Body protection

See Other protection below

Other protection

- Overalls P.V.C. apron.
- Barrier cream.

Respiratory protection

Particulate. (AS/NZS 1716 & 1715, EN 143:2000 & 149:001, ANSI Z88 or national equivalent)

Required Minimum Protection Factor Half-Face Respirator **Full-Face Respirator** Powered Air Respirator PAPR-P1 up to 10 x FS Air-line* up to 50 x ES Air-line* P2 PAPR-P2 up to 100 x ES Air-line PAPR-P3 Air-line**

* - Negative pressure demand ** - Continuous flow

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Respirators may be necessary when engineering and administrative controls do not adequately prevent exposures.
- The decision to use respiratory protection should be based on professional judgment that takes into account toxicity information, exposure measurement data, and frequency and likelihood of the worker's exposure - ensure users are not subject to high thermal loads which may result in heat stress or distress due to personal protective equipment (powered, positive flow, full face apparatus may be an option).
- Published occupational exposure limits, where they exist, will assist in determining the adequacy of the selected respiratory protection. These may be government mandated or vendor recommended.
- Certified respirators will be useful for protecting workers from inhalation of particulates when properly selected and fit tested as part of a complete respiratory protection
- Use approved positive flow mask if significant quantities of dust becomes airborne.
- ▶ Try to avoid creating dust conditions.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Divided Solid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	165	Viscosity (cSt)	Not Applicable
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	218.33

Version No: 2.2

Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS)

Issue Date: **12/09/2018**Print Date: **12/09/2018**

Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Applicable
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Applicable	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

wounds, lesions or abrasions. uts, abraded or irritated skin should not be exposed to this material to the blood-stream, through, for example, cuts, abrasions or lesions, r ne material and ensure that any external damage is suitably protected. uterial can cause eye irritation and damage in some persons. rm exposure to respiratory irritants may result in airways disease, invoice accumulation, in the human body, may occur and may cause some	EC Directives); the material may still produce health damage following entry may produce systemic injury with harmful effects. Examine the skin prior to the oliving difficulty breathing and related whole-body problems. I concern following repeated or long-term occupational exposure. unction i.e. pneumoconiosis, caused by particles less than 0.5 micron
terial may accentuate any pre-existing dermatitis condition intact is not thought to have harmful health effects (as classified under wounds, lesions or abrasions. uts, abraded or irritated skin should not be exposed to this material to the blood-stream, through, for example, cuts, abrasions or lesions, remematerial and ensure that any external damage is suitably protected. Iterial can cause eye irritation and damage in some persons. The exposure to respiratory irritants may result in ainways disease, involve accumulation, in the human body, may occur and may cause some mexposure to high dust concentrations may cause changes in lung fitting and remaining in the lung.	may produce systemic injury with harmful effects. Examine the skin prior to the olving difficulty breathing and related whole-body problems. concern following repeated or long-term occupational exposure. unction i.e. pneumoconiosis, caused by particles less than 0.5 micron
rm exposure to respiratory irritants may result in airways disease, invo- ice accumulation, in the human body, may occur and may cause some rm exposure to high dust concentrations may cause changes in lung fi ting and remaining in the lung.	concern following repeated or long-term occupational exposure. unction i.e. pneumoconiosis, caused by particles less than 0.5 micron
ice accumulation, in the human body, may occur and may cause some rm exposure to high dust concentrations may cause changes in lung fi ting and remaining in the lung.	concern following repeated or long-term occupational exposure. unction i.e. pneumoconiosis, caused by particles less than 0.5 micron
	is but there is not enough data to make an assessment.
CITY	IRRITATION
railable	Not Available
CITY	IRRITATION
railable	Not Available
	2.* Value obtained from manufacturer's SDS. Unless otherwise specified s
C	vailable CITY vailable e obtained from Europe ECHA Registered Substances - Acute toxicity stracted from RTECS - Register of Toxic Effect of chemical Substances. e-like symptoms may continue for months or even years after exposure

Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS) Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.

3-(TRIMETHYLSILYL)-1-PROPANESULFONIC ACID, SODIUM

No significant acute toxicological data identified in literature search.

CODION			
Acute Toxicity	0	Carcinogenicity	0
Skin Irritation/Corrosion	✓	Reproductivity	0

Version No: 2.2

Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS)

Issue Date: 12/09/2018 Print Date: 12/09/2018

Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0
Mutagenicity	0	Aspiration Hazard	0

Legend:

X − Data available but does not fill the criteria for classification
 v − Data available to make classification

Not Available to make classification

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

Sodium 2,2-dimethyl- 2-silapentane-5-sulfonate (DSS)	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
3-(trimethylsilyl)-1- propanesulfonic acid, sodium	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available

Legend:

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
3-(trimethylsilyl)-1- propanesulfonic acid, sodium	HIGH	HIGH

Bioaccumulative potential

Ingredient	Bioaccumulation
3-(trimethylsilyl)-1- propanesulfonic acid, sodium	LOW (LogKOW = 0.4866)

Mobility in soil

Ingredient	Mobility
3-(trimethylsilyl)-1- propanesulfonic acid, sodium	LOW (KOC = 13.38)

SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
 - Reuse
- ► Recycling
- ► Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- ► DO NOT allow wash water from cleaning or process equipment to enter drains
 - It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.

SECTION 14 TRANSPORT INFORMATION

Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Chemwatch: **9-491932** Page **7** of **7**

Version No: 2.2

Sodium 2,2-dimethyl-2-silapentane-5-sulfonate (DSS)

Issue Date: **12/09/2018**Print Date: **12/09/2018**

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

3-(TRIMETHYLSILYL)-1-PROPANESULFONIC ACID, SODIUM(2039-96-5) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Not Applicable

National Inventory Status

National Inventory	Status
Australia - AICS	N (3-(trimethylsilyl)-1-propanesulfonic acid, sodium)
Canada - DSL	N (3-(trimethylsilyl)-1-propanesulfonic acid, sodium)
Canada - NDSL	Y
China - IECSC	Υ
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	N (3-(trimethylsilyl)-1-propanesulfonic acid, sodium)
Korea - KECI	N (3-(trimethylsilyl)-1-propanesulfonic acid, sodium)
New Zealand - NZIoC	N (3-(trimethylsilyl)-1-propanesulfonic acid, sodium)
Philippines - PICCS	N (3-(trimethylsilyl)-1-propanesulfonic acid, sodium)
USA - TSCA	Υ
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	12/09/2018
Initial Date	01/12/2017

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average

 ${\sf PC-STEL} : {\sf Permissible Concentration-Short Term Exposure Limit}$

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

end of SDS