

### Novachem Pty Ltd

#### Version No: 2.3

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: 06/09/2018 Print Date: 06/09/2018 S.GHS.AUS.EN

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### **Product Identifier**

Product name	,2-TETRACHLOROETHANE-D2 (D, 99.6%)	
Chemical Name	,2,2-tetrachloroethane-d2	
Synonyms	M-35	
Proper shipping name	1,1,2,2-TETRACHLOROETHANE	
Chemical formula	C2-Cl4-D2	
Other means of identification	Not Available	
CAS number	33685-54-0*	

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Laboratory chemical reference material	

# Details of the supplier of the safety data sheet

Registered company name	Novachem Pty Ltd	
Address	25 Crissane Road, Heidelberg West Victoria 3081 Australia	
Telephone	+61384151255	
Fax	+61386250088	
Website	www.novachem.com.au	
Email	novachem@novachem.com.au	

### Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre	
Emergency telephone numbers	13 11 26	
Other emergency telephone numbers	Not Available	

# **SECTION 2 HAZARDS IDENTIFICATION**

### Classification of the substance or mixture

Poisons Schedule	Not Applicable	
Classification <sup>[1]</sup>	Acute Toxicity (Dermal) Category 1, Acute Toxicity (Inhalation) Category 1, Eye Irritation Category 2A, Acute Aquatic Hazard Category 2, Chronic Aquatic Hazard Category 2	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

#### Label elements

Hazard pictogram(s)	

#### Hazard statement(s)

H310	-atal in contact with skin.	
H330	Fatal if inhaled.	
H319	Causes serious eye irritation.	
H411	Toxic to aquatic life with long lasting effects.	

### Precautionary statement(s) Prevention

P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P262	Do not get in eyes, on skin, or on clothing.	
P270	Do not eat, drink or smoke when using this product.	
P271	Use only outdoors or in a well-ventilated area.	

### Precautionary statement(s) Response

, ,	•	
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.	
P310	Immediately call a POISON CENTER or doctor/physician.	
P363	Wash contaminated clothing before reuse.	
P302+P350	IF ON SKIN: Gently wash with plenty of soap and water.	

#### Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

### Precautionary statement(s) Disposal

P501	Dispose of contents/container in accordance with local regulations.	

# SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

### Substances

CAS No	%[weight]	Name
33685-54-0	100	1,1,2,2-tetrachloroethane-d2

#### Mixtures

See section above for composition of Substances

### **SECTION 4 FIRST AID MEASURES**

### Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>Transport to hospital or doctor without delay.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin or hair contact occurs:</li> <li>Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>Quickly remove all contaminated clothing, including footwear.</li> <li>Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>Transport to hospital, or doctor.</li> </ul>
Inhalation	<ul> <li>If furnes or combustion products are inhaled remove from contaminated area.</li> <li>Lay patient down. Keep warm and rested.</li> <li>Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>Transport to hospital, or doctor, without delay.</li> </ul>
Ingestion	<ul> <li>If poisoning occurs, contact a doctor or Poisons Information Centre.</li> <li>Avoid giving milk or oils.</li> <li>Avoid giving alcohol.</li> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

#### Indication of any immediate medical attention and special treatment needed

for intoxication due to Freons/ Halons;

A: Emergency and Supportive Measures

- Maintain an open airway and assist ventilation if necessary
- Treat coma and arrhythmias if they occur. Avoid (adrenaline) epinephrine or other sympathomimetic amines that may precipitate ventricular arrhythmias. Tachyarrhythmias caused by increased myocardial sensitisation may be treated with propranolol, 1-2 mg IV or esmolol 25-100 microgm/kg/min IV.
- Monitor the ECG for 4-6 hours
- B: Specific drugs and antidotes:

There is no specific antidote

C: Decontamination

- Inhalation; remove victim from exposure, and give supplemental oxygen if available.
- Ingestion; (a) Prehospital: Administer activated charcoal, if available. DO NOT induce vomiting because of rapid absorption and the risk of abrupt onset CNS depression. (b) Hospital:

- Administer activated charcoal, although the efficacy of charcoal is unknown. Perform gastric lavage only if the ingestion was very large and recent (less than 30 minutes) D: Enhanced elimination:
- There is no documented efficacy for diuresis, haemodialysis, haemoperfusion, or repeat-dose charcoal. POISONING and DRUG OVERDOSE, Californian Poison Control System Ed. Kent R Olson; 3rd Edition
- Do not administer sympathomimetic drugs unless absolutely necessary as material may increase myocardial irritability.
- No specific antidote.
- Because rapid absorption may occur through lungs if aspirated and cause systematic effects, the decision of whether to induce vomiting or not should be made by an attending physician.
- If lavage is performed, suggest endotracheal and/or esophageal control.
- Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach.
- Treatment based on judgment of the physician in response to reactions of the patient
- + Acute exposures to carbon tetrachloride present, initially, with CNS depression followed by hepatic and renal dysfunction.
- Respiratory depression and cardiac dysrhythmias are an immediate threat to life.
- Since a major fraction of absorbed carbon tetrachloride is exhaled in the first hour, good tidal volumes should be maintained in severely poisoned patients; hyperventilation may be an additional therapeutic modality.
- ▶ Ipecac syrup, lavage, activated charcoal or catharsis may all be used in the first 4 hours.
- Since reactive metabolites may cause hepatorenal toxicity, administration of N-acetyl-L-cysteine may reduce complications. Experience with this therapy is limited. [Ellenhorn and Barceloux: Medical Toxicology]

### **SECTION 5 FIREFIGHTING MEASURES**

#### Extinguishing media

- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

### Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

### Advice for firefighters

Fire Fighting	<ul> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>Wear breathing apparatus plus protective gloves in the event of a fire.</li> <li>Prevent, by any means available, spillage from entering drains or water courses.</li> <li>Use fire fighting procedures suitable for surrounding area.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Combustible.</li> <li>Slight fire hazard when exposed to heat or flame.</li> <li>Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>Combustion products include:</li> <li>carbon dioxide (CO2)</li> <li>hydrogen chloride</li> <li>phosgene</li> <li>other pyrolysis products typical of burning organic material.</li> <li>May emit poisonous fumes.</li> </ul>
HAZCHEM	2X

#### SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

### Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignition sources.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> </ul>
Major Spills	#

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# SECTION 7 HANDLING AND STORAGE

### Precautions for safe handling

Safe handling	<ul> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of exposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> </ul>
Other information	<ul> <li>Store in original containers.</li> <li>Keep containers securely sealed.</li> <li>Store in a cool, dry, well-ventilated area.</li> <li>Store away from incompatible materials and foodstuff containers.</li> </ul>

### Issue Date: 06/09/2018 Print Date: 06/09/2018

# 1,1,2,2-TETRACHLOROETHANE-D2 (D, 99.6%)

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Glass container is suitable for laboratory quantities</li> <li>DO NOT use aluminium or galvanised containers</li> <li>Lined metal can, lined metal pail/ can.</li> <li>Plastic pail.</li> <li>Polyliner drum.</li> <li>Packing as recommended by manufacturer.</li> <li>For low viscosity materials</li> <li>Drums and jerricans must be of the non-removable head type.</li> <li>Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):</li> <li>Removable head packaging;</li> <li>Cans with friction closures and</li> <li>low pressure tubes and cartridges</li> <li>may be used.</li> </ul> All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.
Storage incompatibility	<ul> <li>Haloalkanes: <ul> <li>are highly reactive:some of the more lightly substituted lower members are highly flammable; the more highly substituted may be used as fire suppressants, not always with the anticipated results.</li> <li>may react with the lighter divalent metals to produce more reactive compounds analogous to Grignard reagents.</li> <li>may react on contact with potassium or its alloys - although apparently stable on contact with a wide rage of halocarbons, reaction products may be shock-sensitive and may explode with great violence on light impact; severity generally increases with the degree of halocarbon substitution and potassium-sodium alloys give extremely sensitive mixtures .</li> </ul> </li> <li>BRETHERICK L.: Handbook of Reactive Chemical Hazards <ul> <li>react with metal halides and active metals, eg. sodium (Na), potassium (K), lithium (Li),calcium (Ca), zinc (Zn), powdered aluminium (Al) and aluminium alloys, magnesium (Mg) and magnesium alloys.</li> </ul> </li> <li>Tetrachloroethane: <ul> <li>decomposes slowly on contact with water or moisture forming trichloroacetic acid and hydrochloric acid</li> <li>reacts violently with nitric acid (producing carbon dioxide), nitrates, strong oxidisers, strong alkalis, powdered chemically active metals such as aluminium, barium, beryllium, lithium, sodium and zinc and 2,4-dinitrophenyl sulfide</li> <li>Avoid strong bases. Reacts violently with sodium, potassium, nitrates</li> <li>is incompatible with nitrogen tetroxide, finely divided metals</li> <li>decomposes in UV light, on contact with red-hot metals and at temperatures exceeding 150 C, releasing hydrogen chloride, carbon monoxide and phosgene</li> <li>corrodes metals in the presence of moisture</li> </ul> </li> </ul>

# SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

### **Control parameters**

# OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

# EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
1,1,2,2- TETRACHLOROETHANE-D2 (D, 99.6%)	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
1,1,2,2-tetrachloroethane-d2	Not Available		Not Available	

### Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.		
Personal protection			
Eye and face protection	<ul> <li>Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.</li> <li>Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.</li> <li>Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.</li> <li>Alternatively a gas mask may replace splash goggles and face shields.</li> </ul>		
Skin protection	See Hand protection below		
Hands/feet protection	► Elbow length PVC gloves		

	The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice. Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>Eyewash unit.</li> <li>Barrier cream.</li> <li>Skin cleansing cream.</li> </ul>

### **Respiratory protection**

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

### SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

Appearance	Text		
Physical state	Liquid	Relative density (Water = 1)	1.586
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-43	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	147	Molecular weight (g/mol)	Not Available
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	1.07	Gas group	Not Available
Solubility in water (g/L)	Not Available	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

### SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul> <li>Presence of elevated temperatures.</li> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

### SECTION 11 TOXICOLOGICAL INFORMATION

### Information on toxicological effects

Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severely toxic effects; these may be fatal. The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress. Respiratory irritation and pulmonary oedema may follow inhalation exposures. Human volunteers retain about 97% of inspired tetrachloroethane. Industrial experience with tetrachloroethane is unfavourable. A fatal case of exposure was described as cirrhosis of the liver with superimposed hepatitis. Acute intoxication by halogenated aliphatic hydrocarbons appears to take place over two stages. Signs of a reversible narcosis are evident in the first stage and in the second stage signs of injury to organs may become evident, a single organ alone is (almost) never involved.
	Depression of the central nervous system is the most outstanding effect of most halogenated aliphatic hydrocarbons. Inebriation and excitation, passing into narcosis, is a typical reaction. In severe acute exposures there is always a danger of death from respiratory failure or cardiac arrest due to a tendency to make the heart more susceptible to catecholamines (adrenalin)

Ingestion	The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum. Eight humans, each of whom had ingested 3 ml tetrachloroethane by mistake, became comatose and arreflexic but recovered without any apparent ill-effects.			
Skin Contact	Skin contact with the material may produce severely toxic effects; systemic effects may result following absorption and these may be fatal. The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Dermal exposure to tetrachloroethane leads to dryness, scaling, inflammation and purpuric rash. The calculated human skin permeability coefficient is 9 x 10-3 cm/hr. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.			
Eye	This material can cause eye irritation and damage in some persons.			
Chronic	Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models); nevertheless exposure by all routes should be minimised as a matter of course. Chronic exposure to tetrachloroethane causes jaundice, liver enlargement, fatty degeneration, tissue death and hardening of the liver. Human poisoning can manifest as liver toxicity (gastrointestinal disturbance) or central nervous system symptoms including tremors, vertigo and headache. About half of workers at a penicillin plant who were exposed long-term developed inflammation of the liver. Workers making bangles in India showed a high rate of nervous complaints, with tremors being the most common. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.			
4400				
TETRACHLOROETHANE-D2		RRITATION		
(D, 99.6%)	Not Available	Not Available		
1 1 2 2-tetrachloroethane-d2	TOXICITY	IRRITATION		
.,.,=,=	Not Available Not Available			
Legend:	<ol> <li>Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances</li> </ol>			
1,1,2,2- TETRACHLOROETHANE-D2 (D, 99.6%)	Disinfection byproducts (DBPs) are formed when disinfectants such as chlorine Animal studies have shown that some DBPs cause cancer. To date, several hund Numerous haloalkanes and haloalkenes have been tested for cancer-causing ar	, chloramines and ozone react with organic and inorganic matter in water. dred DBPs have been identified. nd mutation-causing activities.		
1,1,2,2- TETRACHLOROETHANE-D2	The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal testing.			
1,1,2,2- TETRACHLOROETHANE-D2 (D, 99.6%) & 1,1,2,2- TETRACHLOROETHANE-D2	For 1,1,2,2-tetrachloroethane: A number of suicides from drinking 1,1,2,2-tetrachloroethane have been reported, with unconsciousness occurring within 1 hour and death within 3-20 hours. Autopsy showed gross congestion in the gullet, stomach, kidneys, spleen and windpipe, kidney and lungs, and gross swelling in the lungs and kidney. Deaths have also occurred after inhalation, with extreme liver destruction and fatty degeneration. In animals, exposure to concentrations of 0.1% caused death in 6 hours.			
Acute Toxicity	✓ C:	arcinogenicity		
Skin Irritation/Corrosion	© R	Reproductivity		
Serious Eye Damage/Irritation	✓ STOT - Sir	ngle Exposure		
Respiratory or Skin sensitisation	STOT - Repea	ated Exposure		
Mutagenicity	S Aspi	iration Hazard		
	Le	gend: X − Data available but does not fill the criteria for classification → Data available to make classification ○ − Data Not Available to make classification		

### SECTION 12 ECOLOGICAL INFORMATION

Toxicity					
1,1,2,2- TETRACHLOROETHANE-D2 (D, 99.6%)	ENDPOINT Not Available	TEST DURATION (HR) Not Available	SPECIES Not Available	VALUE Not Available	SOURCE Not Available
1,1,2,2-tetrachloroethane-d2	ENDPOINT Not Available	TEST DURATION (HR) Not Available	SPECIES Not Available	VALUE Not Available	SOURCE Not Available
Legend:	Extracted from 1. IUC (QSAR) - Aquatic To (Japan) - Bioconcent	CLID Toxicity Data 2. Europe ECHA Regist xicity Data (Estimated) 4. US EPA, Ecotox ration Data 7. METI (Japan) - Bioconcentra	ered Substances - Ecotoxicolog database - Aquatic Toxicity Dat ation Data 8. Vendor Data	yical Information - Aquatic a 5. ECETOC Aquatic Haz	Toxicity 3. EPIWIN Suite V3.12 ard Assessment Data 6. NITE

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

#### For Haloalkanes:

Atmospheric Fate: Fully, or partially, fluorinated haloalkanes released to the air can restrict heat loss from the Earth's atmosphere by absorbing infrared emissions from the surface. The major fate of haloalkanes in the atmosphere is via breakdown by hydroxyl radicals. These substances react with atmospheric ozone and nitrates, which also causes them to change, (transform). Chlorofluorocarbons, (CFC), haloalkanes can break down into chlorine atoms in the air, which also contribute to ozone destruction.

for 1,1,2,2-Tetrachloroethane: Log Kow: 2.39; Vapor Pressure: 6 hPa: Water Solubility: 2.9 g/L; BCF: 4.2-13.2.

Atmospheric Fate: 1,1,2,2-tetrachloroethane will mainly partition to the atmosphere and has an average atmospheric lifetime of 92 days. Its impact on stratospheric ozone, its greenhouse effect and its contribution to the formation of tropospheric ozone is expected to be low. The substance oxidizes in the atmosphere and the intermediate products phosgene and dichloroacetylchloride are formed.

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
1,1,2,2-tetrachloroethane-d2	HIGH	HIGH

#### Bioaccumulative potential

Ingredient	Bioaccumulation	
1,1,2,2-tetrachloroethane-d2	LOW (LogKOW = 2.1926)	

### Mobility in soil

Ingredient	Mobility
1,1,2,2-tetrachloroethane-d2	LOW (KOC = 106.8)

### SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods	
Product / Packaging disposal	<ul> <li>Containers may still present a chemical hazard/ danger when empty.</li> <li>Return to supplier for reuse/ recycling if possible.</li> <li>Otherwise:</li> <li>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> <li>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</li> <li>A Hierarchy of Controls seems to be common - the user should investigate: <ul> <li>Reduction</li> <li>Reuse</li> <li>Recycling</li> <li>Disposal (if all else fails)</li> </ul> </li> <li>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.</li> <li><b>D NOT</b> allow wash water form cleaning or process equipment to enter drains.</li> <li>It may be necessary to collect all wash water for recycling options and these should be considered first.</li> <li>Where in doubt contact the responsible authority.</li> <li>Recycle wherever possible to consult manufacturer for recycling options.</li> <li>Consult State Land Waste Authority for disposal.</li> <li>Bury or incinerate residue at an approved site.</li> <li>Recycle containers if possible attainers.</li> </ul>

### **SECTION 14 TRANSPORT INFORMATION**

#### Labels Required

	6
Marine Pollutant	
HAZCHEM	2X

### Land transport (ADG)

1 ( )	
UN number	1702
UN proper shipping name	1,1,2,2-TETRACHLOROETHANE
Transport hazard class(es)	Class 6.1 Subrisk Not Applicable
Packing group	II Contraction of the second
Environmental hazard	Environmentally hazardous

### Air transport (ICAO-IATA / DGR)

UN number	1702			
UN proper shipping name	1,1,2,2-Tetrachloroethane	9		
Transport hazard class(es)	ICAO/IATA Class 6.1 ICAO / IATA Subrisk Not Applicable ERG Code 6L			
Packing group	II			
Environmental hazard	Environmentally hazardous			
Special precautions for user	Special provisions         Cargo Only Packing Instructions         Cargo Only Maximum Qty / Pack         Passenger and Cargo Packing Instructions         Passenger and Cargo Maximum Qty / Pack         Passenger and Cargo Limited Quantity Packing Instructions		Not Applicable 661 60 L 654 5 L Y641	
	Passenger and Cargo Limited Maximum Qty / Pack		1L	

### Sea transport (IMDG-Code / GGVSee)

UN number	1702	1702		
UN proper shipping name	1,1,2,2-TETRACHLO	ROETHANE		
Transport hazard class(es)	IMDG Class	5.1 Not Applicable		
Packing group	II			
Environmental hazard	Marine Pollutant			
Special precautions for user	EMS Number Special provisions Limited Quantities	F-A , S-A Not Applicable 100 mL		

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

### SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

1,1,2,2-TETRACHLOROETHANE-D2(33685-54-0) IS FOUND ON THE FOLLOWING REGULATORY LISTS Not Applicable

### **National Inventory Status**

National Inventory	Status
Australia - AICS	N (1,1,2,2-tetrachloroethane-d2)
Canada - DSL	N (1,1,2,2-tetrachloroethane-d2)
Canada - NDSL	N (1,1,2,2-tetrachloroethane-d2)
China - IECSC	N (1,1,2,2-tetrachloroethane-d2)
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (1,1,2,2-tetrachloroethane-d2)
Korea - KECI	N (1,1,2,2-tetrachloroethane-d2)
New Zealand - NZIoC	Y
Philippines - PICCS	N (1,1,2,2-tetrachloroethane-d2)
USA - TSCA	N (1,1,2,2-tetrachloroethane-d2)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

### **SECTION 16 OTHER INFORMATION**

Revision Date 06/

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chernwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

 $\mathsf{PC-TWA}:$  Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

Initial Date

06/02/2017

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit\_  $\ensuremath{\mathsf{IDLH}}$  Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection

OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

