

# Sodium Deuteroxide (D, 99.5%) 40% in D20

**Novachem Pty Ltd** 

Version No: **2.2**Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: **12/09/2018**Print Date: **12/09/2018**S.GHS.AUS.EN

# SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier				
Product name Sodium Deuteroxide (D, 99.5%) 40% in D20				
Chemical Name sodium deuteroxide				
Synonyms	DLM-45			
Proper shipping name	SODIUM HYDROXIDE, SOLID			
Chemical formula	D-Na-O			
Other means of identification	Not Available			
CAS number	14014-06-3*			

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses For professional use only. Industrial.

#### Details of the supplier of the safety data sheet

Registered company name	Novachem Pty Ltd			
Address	Crissane Road, Heidelberg West Victoria 3081 Australia			
Telephone	4151255			
Fax	+61386250088			
Website	www.novachem.com.au			
Email	novachem@novachem.com.au			

# Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre
Emergency telephone numbers	13 11 26
Other emergency telephone numbers	Not Available

# **SECTION 2 HAZARDS IDENTIFICATION**

#### Classification of the substance or mixture

Poisons Schedule	S6			
Classification [1]	Skin Corrosion/Irritation Category 1A, Acute Aquatic Hazard Category 3			
Legend: 1. Classified by Chemwatch; 2. Classification drawn from HSIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI				

# Label elements

Hazard pictogram(s)



SIGNAL WORD DANGE

#### Hazard statement(s)

H314	Causes severe skin burns and eye damage.
H402	Harmful to aquatic life.

Chemwatch: 9-487627 Page 2 of 9 Issue Date: 12/09/2018 Version No. 2.2 Print Date: 12/09/2018

#### Sodium Deuteroxide (D, 99.5%) 40% in D20

Page	Double of the last website the control of the contr			
P260	Do not breathe dust/fume/gas/mist/vapours/spray.			
P280	P280 Wear protective gloves/protective clothing/eye protection/face protection.			
P273 Avoid release to the environment.				
Precautionary statement(s) Response				

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.			
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.			
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.				
P310 Immediately call a POISON CENTER or doctor/physician.				

#### Precautionary statement(s) Storage

P405 Store locked up.

# Precautionary statement(s) Disposal

**P501** Dispose of contents/container in accordance with local regulations.

# **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

CAS No	%[weight]	Name sodium deuteroxide	
14014-06-3	40		
7789-20-0*	60	DEUTERIUM OXIDE (D, 99.9%)	

See section above for composition of Substances

#### **SECTION 4 FIRST AID MEASURES**

Description of first aid measures

#### If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Eye Contact Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If skin or hair contact occurs: ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available. **Skin Contact** Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▶ Transport to hospital, or doctor ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary ► Transport to hospital, or doctor.

#### Inhalation

- ▶ Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.
- ► Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).
- As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.
- ▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.

#### This must definitely be left to a doctor or person authorised by him/

# (ICSC13719)

# Ingestion

- For advice, contact a Poisons Information Centre or a doctor at once.
- Urgent hospital treatment is likely to be needed.

#### lowed do **NOT** induce vomitina

- If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
- Observe the patient carefully.
- Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
- Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.
- ► Transport to hospital or doctor without delay.

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For acute or short-term repeated exposures to highly alkaline materials:

- ▶ Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- Oxygen is given as indicated.
- ▶ The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

Chemwatch: 9-487627 Page 3 of 9 Issue Date: 12/09/2018 Version No: 2.2 Print Date: 12/09/2018

#### Sodium Deuteroxide (D, 99.5%) 40% in D20

Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- ▶ Neutralising agents should never be given since exothermic heat reaction may compound injury.
- \* Catharsis and emesis are absolutely contra-indicated.
- \* Activated charcoal does not absorb alkali.
- \* Gastric lavage should not be used.

- Supportive care involves the following:
- Withhold oral feedings initially. If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- ▶ Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

#### **SECTION 5 FIREFIGHTING MEASURES**

#### **Extinguishing media**

- Water spray or fog.
- ► Foam.
- Dry chemical powder.
- ► BCF (where regulations permit).

#### Special hazards arising from the substrate or mixture Fire Incompatibility None known

rife incompatibility	Note Nilowit.
Advice for firefighters	
Fire Fighting	

Fire Fighting	
Fire/Explosion Hazard	<ul> <li>Non combustible.</li> <li>Not considered a significant fire risk, however containers may burn.</li> <li>May emit corrosive fumes.</li> </ul>
HAZCHEM	2W

#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

# Personal precautions, protective equipment and emergency procedures

See section 8

### **Environmental precautions**

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</li> <li>Check regularly for spills and leaks.</li> <li>Clean up all spills immediately.</li> <li>Avoid breathing vapours and contact with skin and eyes.</li> <li>Control personal contact with the substance, by using protective equipment.</li> <li>Contain and absorb spill with sand, earth, inert material or vermiculite.</li> </ul>
Major Spills	<ul> <li>DO NOT touch the spill material</li> <li>Environmental hazard - contain spillage.</li> <li>Clear area of personnel and move upwind.</li> <li>Alert Fire Brigade and tell them location and nature of hazard.</li> <li>May be violently or explosively reactive.</li> </ul>

Personal Protective Equipment advice is contained in Section 8 of the SDS.

### **SECTION 7 HANDLING AND STORAGE**

#### Precautions for safe handling ► Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Safe handling Use in a well-ventilated area. WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material ► DO NOT allow clothing wet with material to stay in contact with skin Store in original containers. ▶ Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Other information Store away from incompatible materials and foodstuff containers DO NOT store near acids, or oxidising ager ▶ No smoking, naked lights, heat or ignition sources

# Conditions for safe storage, including any incompatibilities

Suitable container

- ► Glass container is suitable for laboratory quantities
- ▶ DO NOT use aluminium, galvanised or tin-plated containers

Chemwatch: 9-487627 Page 4 of 9 Issue Date: 12/09/2018 Version No: 2.2

#### Sodium Deuteroxide (D, 99.5%) 40% in D20

Print Date: 12/09/2018

- ▶ Lined metal can, lined metal pail/ can.
- Plastic pail.
- ▶ Polvliner drum.
- Packing as recommended by manufacturer.

For low viscosity materials

- Drums and ierricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging:
- Cans with friction closures and
- ► low pressure tubes and cartridges

may be used

Sodium hydroxide/ potassium hydroxide:

- reacts with water evolving heat and corrosive fumes
- reacts violently with acids, trans-acetylene dichloride, aminotetrazole, p-bis(1,3-dibromoethyl), benzene, bromoform, halogenated compounds, nitrogencontaining compounds, organic halogens, chlorine dioxide ((explodes), chloroform, cresols, cyclopentadiene, 4-chloro-2-methylphenol, cis-dichloroethylene, 2,2-dichloro-3,3-dimethylbutane, ethylene chlorohydrin, germanium, iodine pentafluoride, maleic anhydride, p-nitrotoluene,nitrogen trichloride, o-nitrophenol, phosphonium iodide, potassium peroxodisulfate, propylene oxide, 1,2,4,5-tetrachlorobenzene (highly toxic substance is forme), 2,2,3,3-tetrafluoro-1-propanol, tetrahydrofuran, thorium dicarbide, trichloroethanol, 2,4,6-trinitrotoluene, vinyl acetate
- reacts with fluorine, nitroalkanes, (forming explosive compounds)
- incompatible with acetic acid, acetaldehyde, acetic anhydride, acrolein, acrylonitrile, allyl chloride, organic anhydride, acrylates, alcohols, aldehydes, alkylene oxides, substituted allyls, ammonium chloroplatinate, benzanthrone, bromine, benzene-1,4-diol, carbon dioxide, cellulose nitrate, chlorine trifluoride, 4-chlorobutyronitrile, chlorohydrin, chloronitrotoluenes, chlorosulfonic acid, cinnamaldehyde, caprolactam solution, chlorocresols. 1,2-dichloroethylene, epichlorohydrin, ethylene cyanohydrin, formaldehyde (forms formic acid and flammable hydrogen gas), glycols, glycval, hexachloroplatinate, hydrogen sulfide, hydroquinone, iron-silicon, isocyanates, ketones, methyl azide, 4-methyl-2-nitrophenol, mineral acids (forming corresponding salt), nitrobenzene, N-nitrosohydroxylamine, nitrates pentol, phenols, phosphorus, phosphorus pentaoxide, beta-propiolactone, sodium,  $sulfur\ dioxide,\ tetrahydroborate,\ 1,1,1,2-tetrachloroethane,\ 2,2,2-trichloroethanol,\ trichloronitromethane,\ zirconium$
- ignites on contact with cinnamaldehyde or zinc and reacts explosively with a mixture of chloroform and methane
- forms heat-, friction-, and/ or shock-sensitive- explosive salts with nitro-compounds, cyanogen azide, 3-ethyl-4-hydroxy-1,2,5-oxadiazole, 3-methyl- $\hbox{2-penten-4-yn-1-ol, N,N'-bis (2,2,2-trinitroethyl) urea, trichloroethylene (forms \ dichloroacetylene)}\\$
- increase the explosive sensitivity of nitromethane
- attacks some plastics, rubber, coatings and metals: aluminium, tin, zinc,etc, and their alloys, producing flammable hydrogen gas
- In presence of moisture, the material is corrosive to aluminium, zinc and tin producing highly flammable hydrogen gas
- Reacts vigorously with acids
- Avoid strong acids, acid chlorides, acid anhydrides and chloroformates.
- Avoid contact with copper, aluminium and their alloys.

#### **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

#### Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

Storage incompatibility

INGREDIENT DATA

Not Available

# **EMERGENCY LIMITS**

Ingredient	Material name	IEEL-1		TEEL-2	TEEL-3
sodium deuteroxide	Sodium deuteroxide	0.5 mg/m3		5 mg/m3	50 mg/m3
Ingredient	Original IDLH		Revised IDLH		
sodium deuteroxide	Not Available  Not Available		Not Available		
DEUTERIUM OXIDE (D, 99.9%)			Not Available		

#### Exposure controls

#### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.

#### Personal protection









▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots



# Eye and face protection

- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under
- ▶ Chemical goggles whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.
- Alternatively a gas mask may replace splash goggles and face shields.

# Skin protection

# See Hand protection below

#### ▶ Elbow length PVC gloves

# Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final

Chemwatch: 9-487627 Page 5 of 9 Issue Date: 12/09/2018 Version No: 2.2 Print Date: 12/09/2018

# Sodium Deuteroxide (D, 99.5%) 40% in D20

	choice. Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	<ul> <li>Overalls.</li> <li>PVC Apron.</li> <li>PVC protective suit may be required if exposure severe.</li> <li>Eyewash unit.</li> </ul>

# Respiratory protection

Not Applicable

### **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

# Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Applicable
pH (as supplied)	13-14	Decomposition temperature	Not Available
Melting point / freezing point (°C)	0	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	100	Molecular weight (g/mol)	20.03
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Negligible.	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Applicable
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 TOXICOLOGICAL INFORMATION**

# Information on toxicological effects

Inhaled	Inhaling corrosive bases may irritate the respiratory tract. Symptoms include cough, choking, pain and damage to the mucous membrane.  The material has NOT been classified by EC Directives or other classification systems as "harmful by inhalation". This is because of the lack of corroborating animal or human evidence.  The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage.
Ingestion	Ingestion of alkaline corrosives may produce burns around the mouth, ulcerations and swellings of the mucous membranes, profuse saliva production, with an inability to speak or swallow. Both the oesophagus and stomach may experience burning pain; vomiting and diarrhoea may follow.  The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence.
Skin Contact	The material can produce severe chemical burns following direct contact with the skin.  Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions.  Skin contact with alkaline corrosives may produce severe pain and burns; brownish stains may develop. The corroded area may be soft, gelatinous and necrotic; tissue destruction may be deep.  Open cuts, abraded or irritated skin should not be exposed to this material  Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.  The material may cause severe inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.

Chemwatch: 9-487627 Page 6 of 9 Issue Date: 12/09/2018 Version No: 2.2 Print Date: 12/09/2018

#### Sodium Deuteroxide (D, 99.5%) 40% in D20

Direct eye contact with corrosive bases can cause pain and burns. There may be swelling, epithelium destruction, clouding of the comea and inflammation Eve of the iris. Mild cases often resolve; severe cases can be prolonged with complications such as persistent swelling, scarring, permanent cloudiness, bulging of the eye, cataracts, eyelids glued to the eyeball and blindness. Repeated or prolonged exposure to corrosives may result in the erosion of teeth, inflammatory and ulcerative changes in the mouth and necrosis (rarely) of Chronic the jaw. Bronchial irritation, with cough, and frequent attacks of bronchial pneumonia may ensue. TOXICITY IRRITATION Sodium Deuteroxide (D, 99.5%) 40% in D20 Not Available Not Available TOXICITY IRRITATION sodium deuteroxide Not Available Not Available TOXICITY IRRITATION **DEUTERIUM OXIDE (D, 99.9%)** Not Available Not Available Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.\* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis SODIUM DEUTEROXIDE The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration. **DEUTERIUM OXIDE (D, 99.9%)** No significant acute toxicological data identified in literature search. Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as Sodium Deuteroxide (D. 99.5%) reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing 40% in D20 & SODIUM RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to **DEUTEROXIDE** hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. 0 Carcinogenicity 0 **Acute Toxicity** Skin Irritation/Corrosion Reproductivity Serious Eye Damage/Irritation 0 STOT - Single Exposure Respiratory or Skin 0 STOT - Repeated Exposure 0 sensitisation 0 Mutagenicity **Aspiration Hazard** 0

Legend:

💢 – Data available but does not fill the criteria for classification

Data available to make classification

Data Not Available to make classification

# **SECTION 12 ECOLOGICAL INFORMATION**

# Toxicity

Sodium Deuteroxide (D, 99.5%)	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
40% in D20	Not Available	Not Available	Not Available	Not Available	Not Available
sodium deuteroxide	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
DEUTERIUM OXIDE (D, 99.9%)	ENDPOINT	TEST DURATION (HR)	SPECIES	VALUE	SOURCE
	Not Available	Not Available	Not Available	Not Available	Not Available
	,	<u> </u>			
I edend:	Extracted from 1 IUC	CLID Toxicity Data 2 Furope FCHA Regist	ered Substances - Ecotoxicolog	gical Information - Aquatic	Toxicity 3 FPIWIN Suite V
Legend:		CLID Toxicity Data 2. Europe ECHA Registo exicity Data (Estimated) 4. US EPA, Ecotox			

Harmful to aquatic organisms Prevent, by any means available, spillage from entering drains or water courses.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
DEUTERIUM OXIDE (D, 99.9%)	LOW	LOW

(Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

Version No: 2.2

# Page 7 of 9 Sodium Deuteroxide (D, 99.5%) 40% in D20

Issue Date: **12/09/2018**Print Date: **12/09/2018** 

Ingredient	Bioaccumulation
DEUTERIUM OXIDE (D, 99.9%)	LOW (LogKOW = -1.38)

#### Mobility in soil

Ingredient	Mobility
DEUTERIUM OXIDE (D, 99.9%)	LOW (KOC = 14.3)

### **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- ▶ Reduction
- ▶ Reuse
- ► Recycling
- ► Disposal (if all else fails)

Product / Packaging disposal

- This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- ▶ It may be necessary to collect all wash water for treatment before disposal.
- ▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- ▶ Where in doubt contact the responsible authority.
- ▶ Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- ► Treat and neutralise at an approved treatment plant.
- Treatment should involve: Neutralisation with suitable dilute acid followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).

# **SECTION 14 TRANSPORT INFORMATION**

### **Labels Required**



Marine Pollutant	NO
HAZCHEM	2W

#### Land transport (ADG)

UN number	823		
UN proper shipping name	SODIUM HYDROXIDE, SOLID		
Transport hazard class(es)	Class 8 Subrisk Not Applicable		
Packing group			
Environmental hazard	Not Applicable		
Special precautions for user	Special provisions Not Applicable  Limited quantity 1 kg		

### Air transport (ICAO-IATA / DGR)

UN number	1823			
UN proper shipping name	Sodium hydroxide, solid	Sodium hydroxide, solid		
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	8 Not Applicable		
Desking grann	ERG Code	8L		
Packing group				
Environmental hazard	Not Applicable			
	Special provisions		Not Applicable	
	Cargo Only Packing Instructions		863	
Special precautions for user	Cargo Only Maximum Qty / Pack		50 kg	
	Passenger and Cargo Packing Instructions		859	
	Passenger and Cargo	Maximum Qty / Pack	15 kg	

Chemwatch: 9-487627 Page 8 of 9 Issue Date: 12/09/2018 Version No: 2.2 Print Date: 12/09/2018

### Sodium Deuteroxide (D, 99.5%) 40% in D20

Passenger and Cargo Limited Quantity Packing Instructions Y844 Passenger and Cargo Limited Maximum Qty / Pack 5 kg

#### Sea transport (IMDG-Code / GGVSee)

UN number	1823		
UN proper shipping name	SODIUM HYDROXIDE, SOLID		
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable		
Packing group			
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number F-A , S-B Special provisions Not Applicable Limited Quantities 1 kg		

#### Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

### **SECTION 15 REGULATORY INFORMATION**

Safety, health and environmental regulations / legislation specific for the substance or mixture

SODIUM DEUTEROXIDE(14014-06-3) IS FOUND ON THE FOLLOWING REGULATORY LISTS

# $\|$ DEUTERIUM OXIDE (D, 99.9%)(7789-20-0\*) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Inventory of Chemical Substances (AICS)

#### **National Inventory Status**

National Inventory	Status
Australia - AICS	N (sodium deuteroxide)
Canada - DSL	N (sodium deuteroxide)
Canada - NDSL	N (sodium deuteroxide; DEUTERIUM OXIDE (D, 99.9%))
China - IECSC	N (sodium deuteroxide)
Europe - EINEC / ELINCS / NLP	Υ
Japan - ENCS	N (sodium deuteroxide; DEUTERIUM OXIDE (D, 99.9%))
Korea - KECI	N (sodium deuteroxide)
New Zealand - NZIoC	Υ
Philippines - PICCS	N (sodium deuteroxide; DEUTERIUM OXIDE (D, 99.9%))
USA - TSCA	N (sodium deuteroxide)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

#### **SECTION 16 OTHER INFORMATION**

Revision Date	12/09/2018
Initial Date	17/11/2017

## Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

# **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit.

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL: No Observed Adverse Effect Level

LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value

LOD: Limit Of Detection OTV: Odour Threshold Value

Continued...

Chemwatch: 9-487627 Page 9 of 9 Issue Date: 12/09/2018 Version No: 2.2 Print Date: 12/09/2018

Sodium Deuteroxide (D, 99.5%) 40% in D20

BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.