

Novachem Pty Ltd

Version No: 3.4

Safety Data Sheet according to WHS and ADG requirements

Chemwatch Hazard Alert Code: 4

Issue Date: **16/04/2018** Print Date: **16/04/2018** S.GHS.AUS.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	(±)-11-Hydroxy-Δ9-THC
Chemical Name	(+/-)-11-HYDROXY-DELTA9-THC
Synonyms	H-027
Proper shipping name	METHANOL
Other means of identification	Not Available
CAS number	34675-49-5*

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Laboratory chemicals, Synthesis of substances

Details of the supplier of the safety data sheet

Registered company name	Novachem Pty Ltd	
Address	5 Crissane Road, Heidelberg West Victoria 3081 Australia	
Telephone	+61384151255	
Fax	+61386250088	
Website	www.novachem.com.au	
Email	novachem@novachem.com.au	

Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre	
Emergency telephone numbers	13 11 26	
Other emergency telephone numbers	Not Available	

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Poisons Schedule	\$9	
Classification ^[1]	Flammable Liquid Category 2, Acute Toxicity (Oral) Category 3, Acute Toxicity (Dermal) Category 3, Acute Toxicity (Inhalation) Category 3, Reproductive Toxicity Category 2, Specific target organ toxicity - single exposure Category 1	
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HSIS ; 3. Classification drawn from EC Directive 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)	
SIGNAL WORD	DANGER

Hazard statement(s)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H361	Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

Precautionary statement(s) Prevention

P201	P201 Obtain special instructions before use.	
1 201		
P210	P210 Keep away from heat/sparks/open flames/hot surfaces No smoking.	
P260	Do not breathe dust/fume/gas/mist/vapours/spray.	
P270	Do not eat, drink or smoke when using this product.	

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.	
P307+P311	IF exposed: Call a POISON CENTER or doctor/physician.	
P308+P313	IF exposed or concerned: Get medical advice/attention.	
P330	Rinse mouth.	

Precautionary statement(s) Storage

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

Dispose of contents/container in accordance with local regulations.

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

P501

Substances

CAS No	%[weight]	Name
67-56-1	99.9	methanol
34675-49-5*	0.1	(±)-11-Hydroxy-Δ9-THC

Mixtures

See section above for composition of Substances

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	 If skin or hair contact occurs: Quickly but gently, wipe material off skin with a dry, clean cloth. Immediately remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.
Inhalation	 If furnes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay.
Ingestion	 IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. For advice, contact a Poisons Information Centre or a doctor. Urgent hospital treatment is likely to be needed. In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the SDS should be provided. Further action will be the responsibility of the medical specialist. If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the SDS. Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise: INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. NOTE: Wear a protective glove when inducing vomiting by mechanical means. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

For acute and short term repeated exposures to methanol:

- Toxicity results from accumulation of formaldehyde/formic acid.
- Clinical signs are usually limited to CNS, eyes and GI tract Severe metabolic acidosis may produce dyspnea and profound systemic effects which may become intractable. All symptomatic patients should have arterial pH measured. Evaluate airway, breathing and circulation.
- Stabilise obtunded patients by giving naloxone, glucose and thiamine.
- Decontaminate with Ipecac or lavage for patients presenting 2 hours post-ingestion. Charcoal does not absorb well; the usefulness of cathartic is not established.
- Forced diuresis is not effective; haemodialysis is recommended where peak methanol levels exceed 50 mg/dL (this correlates with serum bicarbonate levels below 18 meq/L).
- Ethanol, maintained at levels between 100 and 150 mg/dL, inhibits formation of toxic metabolites and may be indicated when peak methanol levels exceed 20 mg/dL. An intravenous solution of ethanol in D5W is optimal.
- Folate, as leucovorin, may increase the oxidative removal of formic acid. 4-methylpyrazole may be an effective adjunct in the treatment. 8. Phenytoin may be preferable to diazepam for controlling seizure.

[Ellenhorn Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

Determinant	Index	Sampling Time	Comment
1. Methanol in urine	15 mg/l	End of shift	B, NS
2. Formic acid in urine	80 mg/gm creatinine	Before the shift at end of workweek	B, NS

B: Background levels occur in specimens collected from subjects NOT exposed.

NS: Non-specific determinant - observed following exposure to other materials.

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

Water may be an ineffective extinguishing media for methanol fires; static explosions are reported for aqueous solutions as dilute as 30%. Water may be used to cool containers.

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility	Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
Advice for firefighters	
Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus. Prevent, by any means available, spillage from entering drains or water course.
Fire/Explosion Hazard	 Liquid and vapour are highly flammable. Severe fire hazard when exposed to heat, flame and/or oxidisers. Vapour may travel a considerable distance to source of ignition. Heating may cause expansion or decomposition leading to violent rupture of containers. Combustion products include: carbon dioxide (CO2) formaldehyde other pyrolysis products typical of burning organic material.
HAZCHEM	•2WE

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Remove all ignition sources. Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment.
Major Spills	 Clear area of personnel and move upwind. Alert Fire Brigade and tell them location and nature of hazard. May be violently or explosively reactive. Wear full body protective clothing with breathing apparatus.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 HANDLING AND STORAGE

Safe handling	 Containers, even those that have been emptied, may contain explosive vapours. Do NOT cut, drill, grind, weld or perform similar operations on or near containers. Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps.
Other information	 Store in original containers in approved flame-proof area. No smoking, naked lights, heat or ignition sources. DO NOT store in pits, depressions, basements or areas where vapours may be trapped. Keep containers securely sealed.

Conditions for safe storage, including any incompatibilities

Suitable container	 Glass container is suitable for laboratory quantities Packing as supplied by manufacturer. Plastic containers may only be used if approved for flammable liquid. Check that containers are clearly labelled and free from leaks. For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) For manufactured product having a viscosity of at least 250 cSt.
Storage incompatibility	 Methanol: reacts violently with strong oxidisers, acetyl bromide, alkyl aluminium salts, beryllium dihydride, bromine, chromic acid, 1-chloro-3,3-difluoro-2-methoxycyclopropene, cyanuric chloride, diethylzinc, isophthaloyl chloride, nitric acid, perchloric acid, potassium-tert-butoxide, potassium sulfur diimide, Raney nickel catalysts, 2,4,6-trichlorotriazine, triethylaluminium, 1,3,3-trifluoro-2-methoxycyclopropene is incompatible with strong acids, strong caustics, alkaline earth and alkali metals, aliphatic amines, acetaldehyde, benzoyl peroxide, 1,3-bis(dinn-cyclopentadienyl iron)-2-propen-1-one, calcium carbide, chloroform, chromic anhydride, chromium trioxide, dialkylzinc, dichlorine oxide, dichloromethane, ethylene oxide, hypochlorous acid, isocyanates, isopropyl chlorocarbonate, lithium tetrahydroaluminate, magnesium, methyl azide, nitrogen dioxide, palladium, pentafluoroguanidine, perchloryl fluoride, phosphorus pentasulfide, phosphorus trioxide, potassium, tangerine oil, triisobutylaluminium mixtures with lead perchlorate, sodium hypochlorite are explosive may react with metallic aluminium at high temperatures slowly corrodes lead and aluminium may generate electrostatic charges, due to low conductivity, on flow or agitation attacks some plastics, rubber and coatings. Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content Alcohols are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents. reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen reacts, possibly violently, with alkaline metals, and alkaline earth metals to produce hydrogen reacts, possibly violently, with alkaline metals and alkaline earth m

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA									
Source	Ingredient	Material name TWA		STEL		Peak		Notes	
Australia Exposure Standards	methanol	Methyl alcohol 262 mg/m3 / 200 ppm		328 mg/m3 / 250 ppm		Not Available		Not Available	
EMERGENCY LIMITS									
Ingredient	Material name		TEEL-1		TEEL-2		TEEL-3		
methanol	Methyl alcohol; (N	d alcohol; (Methanol)		Not Available Not Av		Not Available		Not Ava	ilable
Ingredient	Original IDLH	Original IDLH		Revised IDLH					
methanol	6000 ppm	6000 ppm			Not Available				
(±)-11-Hydroxy-Δ9-THC	Not Available		Not Available						

Exposure controls

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	 Safety glasses with side shields Chemical goggles. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience.

Skin protection	See Hand protection below
Hands/feet protection	 Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber Personal hygiene is a key element of effective hand care.
Body protection	See Other protection below
Other protection	 Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity. For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets). Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

(±)-11-Hydroxy- Δ 9-THC

Material	CPI
BUTYL	A
BUTYL/NEOPRENE	А
PE/EVAL/PE	A
PVDC/PE/PVDC	А
SARANEX-23 2-PLY	A
SARANEX-23	A
TEFLON	A
VITON/NEOPRENE	A
NEOPRENE	В
NAT+NEOPR+NITRILE	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE	С
PVA	С
PVC	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final

selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Not Available		
Physical state	Liquid	Relative density (Water = 1)	0.79 @ 20 C
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	385- (464 ICI)
pH (as supplied)	Not Applicable	Decomposition temperature	Not Available
Melting point / freezing point (°C)	-97.8	Viscosity (cSt)	0.59
Initial boiling point and boiling range (°C)	64-65	Molecular weight (g/mol)	32.04
Flash point (°C)	9.7	Taste	Not Available
Evaporation rate	2.1 BuAc=1 BuAC = 1	Explosive properties	Not Available
Flammability	HIGHLY FLAMMABLE.	Oxidising properties	Not Available

Respiratory protection

Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content. The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.

Upper Explosive Limit (%)	36	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	6	Volatile Component (%vol)	ca 100 @ 20 C
Vapour pressure (kPa)	12.26 @ 20 C	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Neutral
Vapour density (Air = 1)	1.1	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	 Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content. Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and grygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Inhaled Inimitable of the individual system optic nerves and refinae. Symptoms may be delayed, with headache, nausea, bluring of vision and double vision. Continued or severe exposures may cause damage to optic nerves, which may become severe with pervisual impairment even blindness resulting. WARNING: Methanol is only slowly eliminated from the body and should be regarded as a cumulative poison which cannot be made non-harmful [CCI/NFO] Inhaled Toxic effects may result from the accidental ingestion of the material during the course of normal handling, may produce toxic effects. There is strong evidence to suggest that this material can cause, if inhaled once, serious, irreversible damage of organs. Toxic effects may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fate produce sociaus damage to the health of the individual. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC1373 Methanol may produce a burning or painful sensation in the mouth, throat, chest, and stomach. This may be accompanied by nausea, vorning, her dizziness, shortness of breath, weakness, faigue, leg camps, restlessness, confusion, drunken behaviour, visual disturbance, drowsiness, coma death. Skin contact Skin contact with the material may produce toxic effects; systemic effects may result folowing absorption. The material is not thou	-					
Imposition produce serious damage to the health of the individual. Swellowing of the liquid ray course aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result (ICSC1373 Methanol may produce a burning or paintul sensation in the mouth, threat, chest, and stomach. This may be accompanied by nausea, vomiting, here datarines, shortness of breach, weakness, fatigue, leg camps, restlessness, confusion, dunken behaviour, visual disturbance, drowsiness, coma dearh. Skin contact with the material may produce toxic effects; systemic effects may result following absorption. The material is not thought to be a skin initiant (as classified by EC Directives using animal models). Temporary discomfort, however, may result prolonged demail exposures. Open cuts, abraded or imitated skin should not be exposed to this material Entry into the block stream, through, for example, cuts, abraside of contact with skin, can cause serious, ineversible damage of organs. Attrough the liquid is not thought to be an initiant (as classified by EC Directives), direct contact with the eye may produce transient discomfort characterised by tearing or conjunctival redness (as with windburn). Stomethy Chronic Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models) and ensure that may also result. (e)-11+Hydroxy-A9-Titc TOXICITY Methanol IRRITATION Methanol ICXICITY Interial is 10, 1050: 15800 mg/kg ^[2] Invalid in (rabbil): 20 mg/24h-moderate Inhalation (rat) LC50: 63928, 976 mg/4h ^[2]	Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. Minor but regular methanol exposures may effect the central nervous system, optic nerves and retinae. Symptoms may be delayed, with headache, fatigue, nausea, blurring of vision and double vision. Continued or severe exposures may cause damage to optic nerves, which may become severe with permanent visual impairment even blindness resulting. WARNING: Methanol is only slowly eliminated from the body and should be regarded as a cumulative poison which cannot be made non-harmful [<i>CCINFO</i>] Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects.				
Skin Contact The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Temporary discontfort, however, may result of prolonged dermal exposures. Open outs, abraded or inflated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abradenor elesions, may produce systemic hijury with harmful effects. Examine the skin price use of the material and ensure that any external damage is suitably protected. There is strong evidence to suggest that this material, on a single contact with skin, can cause serious, irreversible damage of organs. Less of the material and ensure that any external damage is suitably protected. There is strong evidence to suggest that this material, on a single contact with skin, can cause serious, irreversible damage of organs. Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal models). Temporary discontfort characterised by tearing or conjunctival redness (as with windburn). Sittmeth (±)-11+Hydroxy-Δ9-THC TOXICITY IRRITATION Methanol TOXICITY IRRITATION Dermal (rabbit) LD50: 15800 mg/kg ^[2] Eye (rabbit): 100 mg/24h-moderate Dermal (rabbit) LD50: 5600 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate Oral (rat) LD50: 5600 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate Oral (rabbit) LD50: 15800 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate Oral (rat) LD50: 5600 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate	Ingestion	Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733) Methanol may produce a burning or painful sensation in the mouth, throat, chest, and stomach. This may be accompanied by nausea, vomiting, headache, dizziness, shortness of breath, weakness, fatigue, leg cramps, restlessness, confusion, drunken behaviour, visual disturbance, drowsiness, coma and				
Eye characterised by tearing or conjunctival redness (as with windburn). st0meth Chronic Long-term exposure to the product is not thought to produce chronic effects adverse to the health (as classified by EC Directives using animal me nevertheless exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vorniting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double v Liver and/or kidney injury may also result. (t)-11-Hydroxy_Δ9-THC TOXICITY IRRITATION Mot Available Not Available TOXICITY IRRITATION Inalation (rat) LC50: 63926.976 mg/l4h ^[2] Eye (rabbit): 100 mg/24h-moderate (t)-11-Hydroxy_Δ9-THC TOXICITY IRRITATION (t)-11-Hydroxy_Δ9-THC TOXICITY IRRITATION Inalation (rat) LC50: 63926.976 mg/l4h ^[2] Eye (rabbit): 100 mg/24h-moderate (t)-11-Hydroxy_Δ9-THC TOXICITY IRRITATION	Skin Contact	The material is not thought to be a skin irritant (as classified by EC Directives using animal models). Temporary discomfort, however, may result from prolonged dermal exposures. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.				
Chronic Inevertheless exposure by all routes should be minimised as a matter of course. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double volue	Eye	characterised by tearing or conjunctival redness (as with windburn).				
(±)-11-Hydroxy-Δ9-THC Not Available Not Available Interface ICXICITY IRRITATION Dermal (rabbit) LD50: 15800 mg/kg ^[2] Eye (rabbit): 100 mg/24h-moderate Inhalation (rat) LC50: 63926.976 mg/l/4h ^[2] Eye (rabbit): 40 mg-moderate Oral (rat) LD50: 5600 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate TOXICITY IRRITATION Inhalation (rat) LC50: 63926.976 mg/l/4h ^[2] Eye (rabbit): 20 mg/24 h-moderate	Chronic	Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision.				
(±)-11-Hydroxy-Δ9-THC Not Available Not Available Mot Available Not Available IRRITATION methanol Constant of the state of the st						
Not Available Not Available Image: methanol	(+)-11-Hydroxy-A9-THC	ΤΟΧΙΟΙΤΥ	IRRITATION			
Dermal (rabbit) LD50: 15800 mg/kg ^[2] Eye (rabbit): 100 mg/24h-moderate Inhalation (rat) LC50: 63926.976 mg/l/4h ^[2] Eye (rabbit): 40 mg-moderate Oral (rat) LD50: 5600 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate	(<u>_)</u>	Not Available	Not Available			
methanol Inhalation (rat) LC50: 63926.976 mg/l/4h ^[2] Eye (rabbit): 40 mg-moderate Oral (rat) LD50: 5600 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate		тохісіту	IRRITATION			
Inhalation (rat) LC50: 63926.976 mg/l/4h ^[2] Eye (rabbit): 40 mg-moderate Oral (rat) LD50: 5600 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate TOXICITY IRRITATION		Dermal (rabbit) LD50: 15800 mg/kg ^[2]	Eye (rabbit): 100 mg/24h-moderate			
Oral (rat) LD50: 5600 mg/kg ^[2] Skin (rabbit): 20 mg/24 h-moderate (±)-11-Hydroxy-Δ9-THC IRRITATION	methanol	Inhalation (rat) LC50: 63926.976 mg/l/4h ^[2]	Eye (rabbit): 40 mg-moderate			
(±)-11-Hydroxy-Δ9-THC			Skin (rabbit): 20 mg/24 h-moderate			
(±)-11-Hydroxy-Δ9-THC						
	(±)-11-Hydroxy-∆9-THC					
Legend: 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise spectration data extracted from RTECS - Register of Toxic Effect of chemical Substances	Legend:					

(±)-1	1	-Hy	yd	ro	ху	ν-Δ	9-	T	Η	С
----	-----	---	-----	----	----	----	------------	----	---	---	---

METHANOL	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.				
Acute Toxicity	✓	Carcinogenicity	0		
Skin Irritation/Corrosion	\odot	Reproductivity	✓		
Serious Eye Damage/Irritation	0	STOT - Single Exposure	✓		
Respiratory or Skin sensitisation	0	STOT - Repeated Exposure	0		
Mutagenicity	0	Aspiration Hazard	0		
		✓ - D	ata available but does not fill the criteria for classification ata available to make classification ata Not Available to make classification		

SECTION 12 ECOLOGICAL INFORMATION

(4) 11 Hudrowy AO THC	ENDPOINT		TEST DURATION (HR)		SPECIES	VALUE		SOURCE	
(±)-11-Hydroxy-∆9-THC	Not Available Not Available				Not Available	Not Available		Not Available	
	ENDPOINT	TE	ST DURATION (HR)	SPECIE	S		VALUE	SOUR	
	LC50	96	× 7	Fish			>100mg/L	4	
	EC50	48		Crustac	Crustacea		>10000mg/L	4	
methanol	EC50	96		Algae or other aquatic plants		<10000mg/L	. 4		
	BCF	24		Algae or other aquatic plants		0.05mg/L	4		
	EC0	168		Algae or other aquatic plants			=530mg/L	1	
	NOEC	72			Crustacea 0.1mg/L			4	
(+) 44 lbsdmm 40 TUC	ENDPOINT		TEST DURATION (HR)		SPECIES	VALUE	VALUE SOU		
(±)-11-Hydroxy-∆9-THC	Not Available		Not Available		Not Available	Not Avail	able	Not Available	
	Not Available		Not Available		Not Available	Not Avail	able	Not Available	

For Methanol: Log Kow: -0.82 to -0.66; Koc: 1; Henry 🕏 s Law Constant: 4.55x10-6 atm-cu m/mole; Vapor Pressure: 127 mm Hg; BCF: < 10.

Atmospheric Fate: Methanol is expected to exist solely as a vapor in the ambient atmosphere. Vapor-phase methanol is broken down in the atmosphere by reactions with hydroxyl radicals; the half-life for this reaction in air is estimated to be 17 days.

Terrestrial Fate: Methanol is expected to have very high mobility in soil.

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
methanol	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
methanol	LOW (BCF = 10)

Mobility in soil

Ingredient	Mobility
methanol	HIGH (KOC = 1)


SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise:
Product / Packaging disposal	 If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In
some areas, certain wastes must be tracked.
A Hierarchy of Controls seems to be common - the user should investigate:
▶ Reduction
▶ Reuse
► Recycling
▶ Disposal (if all else fails)
This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
DO NOT allow wash water from cleaning or process equipment to enter drains.
It may be necessary to collect all wash water for treatment before disposal.
In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
Where in doubt contact the responsible authority.
Recycle wherever possible.
Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal
facility can be identified.
Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (a)
admixture with suitable combustible material).
Decontaminate empty containers.

SECTION 14 TRANSPORT INFORMATION

Labels Required



•2WE

Marine Pollutant HAZCHEM

Land transport (ADG)

UN number	1230			
UN proper shipping name	METHANOL			
Transport hazard class(es)	Class3Subrisk6.1			
Packing group	l			
Environmental hazard	Not Applicable			
Special precautions for user	Special provisions 279 Limited quantity 1 L			

Air transport (ICAO-IATA / DGR)

UN number 1230	1230		
UN proper shipping name Methanol			
ICAO/IATA Cla	ss 3		
Transport hazard class(es) ICAO / IATA S	orisk 6.1		
ERG Code	3L		
Packing group			
Environmental hazard Not Applicable	Not Applicable		
Special provisi	Special provisions		
Cargo Only Pa	Cargo Only Packing Instructions		
Cargo Only Ma	Cargo Only Maximum Qty / Pack		
Special precautions for user Passenger and	Cargo Pa	cking Instructions	
Passenger and	Passenger and Cargo Maximum Qty / Pack		
Passenger and	Cargo Lin	nited Quantity Packing Instructions	

Sea transport (IMDG-Code / GGVSee)

UN number	1230
UN proper shipping name	METHANOL

Transport hazard class(es)	IMDG Class3IMDG Subrisk6.1
Packing group	ll
Environmental hazard	Not Applicable
Special precautions for user	EMS NumberF-E, S-DSpecial provisions279Limited Quantities1 L

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

METHANOL(67-56-1) IS FOUND ON THE FOLLOWING REGULATORY LISTS

Australia Exposure Standards

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australia Inventory of Chemical Substances (AICS)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix E (Part 2)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Appendix F (Part 3)

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule $\ensuremath{\mathsf{5}}$

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6

(±)-11-HYDROXY-Δ9-THC(34675-49-5*) IS FOUND ON THE FOLLOWING REGULATORY LISTS Not Applicable

National Inventory	Status
Australia - AICS	N ((±)-11-Hydroxy-Δ9-THC)
Canada - DSL	N ((±)-11-Hydroxy-Δ9-THC)
Canada - NDSL	N (methanol; (±)-11-Hydroxy-Δ9-THC)
China - IECSC	N ((±)-11-Hydroxy-Δ9-THC)
Europe - EINEC / ELINCS / NLP	N ((±)-11-Hydroxy-Δ9-THC)
Japan - ENCS	N ((±)-11-Hydroxy-Δ9-THC)
Korea - KECI	N ((±)-11-Hydroxy-Δ9-THC)
New Zealand - NZIoC	N ((±)-11-Hydroxy-Δ9-THC)
Philippines - PICCS	N ((±)-11-Hydroxy-Δ9-THC)
USA - TSCA	N ((±)-11-Hydroxy-Δ9-THC)
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Revision Date	16/04/2018

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC – TWA: Permissible Concentration-Time Weighted Average PC – STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit, IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL: No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value BCF: BioConcentration Factors BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

