

Novachem Pty Ltd

Version No: 1.1

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 04/04/2023 Print Date: 04/04/2023 S.GHS.AUS.EN

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier

Product name	Beryllium ICP-MS Standard	
Synonyms	lot Available	
Proper shipping name	ORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid solution)	
Other means of identification	ICP-MS-05N-0.1X-1	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses Laboratory Chemical Reference Material

Details of the manufacturer or supplier of the safety data sheet

Registered company name	Novachem Pty Ltd	Novachem Pty Ltd
Address 25 Crissane Road, Heidelberg West Victoria 3081 Australia		25 Crissane Road, Heidelberg West Victoria 3081 Australia
Telephone	+61384151255	+61384151255
Fax	+61386250088	+61386250088
Website	www.novachem.com.au	www.novachem.com.au
Email	novachem@novachem.com.au	novachem@novachem.com.au

Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre	Victorian Poisons Information Centre
Emergency telephone numbers	13 11 26	13 11 26
Other emergency telephone numbers	Not Available	Not Available

SECTION 2 Hazards identification

Poisons Schedule Not Applicable		
Classification ^[1]	Carcinogenicity Category 1B, Specific Target Organ Toxicity - Repeated Exposure Category 2, Corrosive to Metals Category 1, Serious Eye Damage/Eye Irritation Category 1, Acute Toxicity (Oral) Category 4, Sensitisation (Skin) Category 1, Acute Toxicity (Inhalation) Category 2, Skin Corrosion/Irritation Category 1A	
Leaend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI	

Label elements

Hazard pictogram(s)	Provide the second seco		

Signal word

Danger

Hazard statement(s)

H350	May cause cancer.	
H373	H373 May cause damage to organs through prolonged or repeated exposure.	
H290	May be corrosive to metals.	
H302	P Harmful if swallowed.	
H317	May cause an allergic skin reaction.	

H330	Fatal if inhaled.
H314	Causes severe skin burns and eye damage.

Precautionary statement(s) Prevention

P201 Obtain special instructions before use.	
P260 Do not breathe mist/vapours/spray.	
P264	Wash all exposed external body areas thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.

Precautionary statement(s) Response

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.		IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
	P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.		IF INHALED: Remove person to fresh air and keep comfortable for breathing.
	P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Precautionary statement(s) Storage

	-
P403+P233 Store in a well-ventilated place. Keep container tightly closed.	
P405 Store locked up.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
19049-40-2	1.127	beryllium acetate, basic
7697-37-2	2	nitric acid
7732-18-5	96.873	water
Legend:	1. Classified by Chernwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L * EU IOELVs available	

SECTION 4 First aid measures

Description of first aid measures If this product comes in contact with the eyes: · Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper Eye Contact and lower lids Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel. If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Skin Contact Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor. If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Inhalation Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. ▶ For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Indestion Observe the patient carefully. Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious. • Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- Acute berylliosis produces interstitial fibrotic disease rather than the simple focal nodular lesions seen in simple pneumoconiosis. Fibrotic lesions appear out of proportion to dust-laden macrophages.
- In common with asbestosis and aluminosis the condition is characterised by reduced lung volumes, elasticity and diffusion. Chronic exposure causes chronic

granulomatous disease similar to sarcoidosis and miliary tuberculosis. Multi-system involvement includes lymph nodes, spleen, liver, myocardium, kidney and bones. Occasionally hypercalcaemia develops. Initially non-specific symptoms appear and are followed by dyspnoea and cough. Symptoms are progressive and steroids may help to blunt the course of the disease.

- ACTH and cortisone therapy have been encouraging. Aurin tricarboxylic acid effectively protects monkeys exposed to lethal quantities of beryllium no data is available for humans to substantiate its safety or effectiveness.
- Medical surveillance for beryllium health effects includes:
- (1) skin examination, (2) respiratory history, (3) examination of the lungs, (4) lung function tests (FVC and FEV1), and (5) periodic chest x-ray.
- In addition, a specialised, specific, immunological blood test, the beryllium blood lymphocyte proliferation test (BLPT), is available to assist in the diagnosis of beryllium related reactions. Individuals who have an abnormal BLPT are normally referred to a lung specialist for additional specific tests to determine if chronic beryllium disease is present.

Note: Substantial inter- and intra-laboratory disagreement exists among the laboratories that conduct this test. The BLPT does not at this time meet the criteria for a screening test. Despite its limitations, however, the BLPT remains a useful disease surveillance tool.

For acute or short term repeated exposures to strong acids

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling

Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.

• Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues. INGESTION:

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury.
- Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping
 Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

- There is no restriction on the type of extinguisher which may be used.
- Use extinguishing media suitable for surrounding area.

Special hazards arising from the substrate or mixture

Fire Incompatibility	None known.
Advice for firefighters	

Fire Fighting	 Alert Fire Brigade and tell them location and nature of hazard. Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses. Use fire fighting procedures suitable for surrounding area.
Fire/Explosion Hazard	 Non combustible. Not considered to be a significant fire risk. Acids may react with metals to produce hydrogen, a highly flammable and explosive gas. Heating may cause expansion or decomposition leading to violent rupture of containers. May emit poisonous fumes.
HAZCHEM	2X

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

Minor Spills	 Clean up all spills immediately. Avoid breathing vapours and contact with skin and eyes. Control personal contact with the substance, by using protective equipment. Contain and absorb spill with sand, earth, inert material or vermiculite.
Major Spills	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

Page 4 of 10

Beryllium ICP-MS Standard

SECTION 7 Handling and storage

Precautions for safe handling			
Safe handling	 Avoid all personal contact, including inhalation. Wear protective clothing when risk of exposure occurs. Use in a well-ventilated area. Prevent concentration in hollows and sumps. 		
Other information	 Store in original containers. Keep containers securely sealed. Store in a cool, dry, well-ventilated area. Store away from incompatible materials and foodstuff containers. 		

Conditions for safe storage, including any incompatibilities

Suitable container	 Lined metal can, lined metal pail/ can. Plastic pail. Polyliner drum. Packing as recommended by manufacturer. For low viscosity materials Drums and jerricans must be of the non-removable head type. Where a can is to be used as an inner package, the can must have a screwed enclosure. For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.): Removable head packaging; Cans with friction closures and Iow pressure tubes and cartridges may be used. All inner and sole packagings for substances that have been assigned to Packaging Groups I or II on the basis of inhalation toxicity criteria, must be hermetically sealed.
Storage incompatibility	Avoid strong bases.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	beryllium acetate, basic	Beryllium & compounds	0.002 mg/m3	Not Available	Not Available	(g) Some compounds in these groups are classified as carcinogenic or as sensitisers. Check individual classification details on the safety data sheet for information on classification.
Australia Exposure Standards	nitric acid	Nitric acid	2 ppm / 5.2 mg/m3	10 mg/m3 / 4 ppm	Not Available	Not Available

Emergency Limits					
Ingredient	TEEL-1	TEEL-2		TEEL-3	
nitric acid	Not Available	Not Available		Not Available	
Ingredient	Original IDLH		Revised IDLH		
beryllium acetate, basic	4 mg/m3		Not Available		
nitric acid	25 ppm		Not Available		
water	Not Available		Not Available		

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Exposure controls

Appropriate engineering controls

"adds" and "removes" air in the work environment.

Individual protection measures, such as personal protective equipment



The basic types of engineering controls are:

Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure.

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically

Chemical goggles.whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted.
 Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face protection.

E-PAPR-2 P2 ^

Continued...

	Alternatively a gas mask may replace splash goggles and face shields.
Skin protection	See Hand protection below
Hands/feet protection	 Elbow length PVC gloves When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. NOTE: The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.
Body protection	See Other protection below
Other protection	 Overalls. Eyewash unit. Barrier cream. Skin cleansing cream.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index". The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Beryllium ICP-MS Standard

Material	CPI
BUTYL	A
NEOPRENE	A
HYPALON	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE/NATURAL	С
NITRILE+PVC	С
PE/EVAL/PE	С
PVA	С
PVC	С
SARANEX-23	С
VITON	С

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

protection varies with Type of filter.					
Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator		
up to 10 x ES	E-AUS P2	-	E-PAPR-AUS / Class 1 P2		
up to 50 x ES	-	E-AUS / Class 1 P2	-		

E-2 P2

Type E-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001,

Where the concentration of gas/particulates in the breathing zone, approaches or

Degree of protection varies with both face-piece and Class of filter; the nature of

exceeds the "Exposure Standard" (or ES), respiratory protection is required.

^ - Full-face

up to 100 x ES

Respiratory protection

ANSI Z88 or national equivalent)

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

Appearance	Clear liquid			
Physical state	Liquid	Relative density (Water = 1)	1.02	
Odour	Not Available	Partition coefficient n-octanol / water	Not Available	
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available	
pH (as supplied)	<2.0	Decomposition temperature (°C)	Not Available	
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available	
Initial boiling point and boiling range (°C)	83	Molecular weight (g/mol)	Not Available	
Flash point (°C)	Not Available	Taste	Not Available	
Evaporation rate	Not Available	Explosive properties	Not Available	
Flammability	Not Available	Oxidising properties	Not Available	

Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	2.47	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	0.62	VOC g/L	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological effects

Inhaled	The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce severe damage to the health of the individual. Relatively small amounts absorbed through the lungs may prove fatal. Inhaled beryllium is not absorbed rapidly. It accumulates in the bones, kidney and liver.	
Ingestion	Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident. The material has NOT been classified by EC Directives or other classification systems as "harmful by ingestion". This is because of the lack of corroborating animal or human evidence. Exposure to even extremely small amounts of beryllium can result in the inhibition of a number of metabolic pathways. Beryllium even in its most highly soluble forms is poorly absorbed from the gastrointestinal tract.	
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Skin contact is not thought to have harmful health effects (as classified under EC Directives); the material may still produce health damage following entry through wounds, lesions or abrasions. Beryllium causes the sensitivity of skin to increase. It is an irritant and causes inflammation on contact, nodules and ulcers. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.	
Eye	Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely. If applied to the eyes, this material causes severe eye damage. Irritation of the eyes may produce a heavy secretion of tears (lachrymation).	
Chronic	Repeated or prolonged exposure to acids may result in the erosion of teeth, swelling and/or ulceration of mouth lining. Irritation of airways to lung, with cough, and inflammation of lung tissue often occurs. Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Long-term exposure to respiratory irritants may result in airways disease, involving difficulty breathing and related whole-body problems. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. Chronic exposure to beryllium dusts and fumes may cause progressive lung damage and systemic disease including inflammation, joint pain, skin lesions, chills, fever, damage to the liver, kidney, spleen, lymph nodes and heart. The onset may be marked by weakness, fatigue, weight loss without cough or shortness of breath. Beryllium causes the sensitivity of skin to increase. It is an irritant and causes inflammation on contact, nodules and ulcers.	
Beryllium ICP-MS Standard	TOXICITY Not Available	IRRITATION Not Available
beryllium acetate, basic	TOXICITY Not Available	IRRITATION Not Available

nitric acid	ΤΟΧΙΟΙΤΥ	IRRITATION
	Inhalation(Rat) LC50: 0.13 mg/L4h ^[2]	Eye: adverse effect observed (irritating) ^[1]
		Skin: adverse effect observed (corrosive) ^[1]
	ΤΟΧΙΟΙΤΥ	IRRITATION
water	Oral (Rat) LD50: >90000 mg/kg ^[2]	Not Available

BERYLLIUM ACETATE, BASIC	WARNING: This substance has been classified by the IARC as Group 1: CARCINOGENIC TO HUMANS.		
NITRIC ACID	Oral (?) LD50: 50-500 mg/kg * [Various Manufacturers] The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis. The material may produce respiratory tract irritation, and result in damage to the lung including reduced lung function. The material may cause severe skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin. Repeated exposures may produce severe ulceration.		
Beryllium ICP-MS Standard & BERYLLIUM ACETATE, BASIC & NITRIC ACID	Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia.		
Beryllium ICP-MS Standard & BERYLLIUM ACETATE, BASIC	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions.		
Beryllium ICP-MS Standard & NITRIC ACID	For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic damage when the pH falls to about 6.5. Cells from the respiratory tract have not been examined in this respect. Mucous secretion may protect the cells of the airway from direct exposure to inhaled acidic mists (which also protects the stomach lining from the hydrochloric acid secreted there).		
BERYLLIUM ACETATE, BASIC & WATER	No significant acute toxicological data identified in liter	ature search.	
Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Serious Eye Damage/Irritation Respiratory or Skin sensitisation	 ✓ ✓ 	STOT - Single Exposure STOT - Repeated Exposure	× •

SECTION 12 Ecological information

	Endpoint	Test Duration (hr)	Species	Value	Source
Beryllium ICP-MS Standard	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
beryllium acetate, basic	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50(ECx)	96h	Crustacea	39mg/l	2
nitric acid	LC50	96h	Fish	102.24mg/L	4
	EC50	48h	Crustacea	490mg/l	2
	Endpoint	Test Duration (hr)	Species	Value	Source
water	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	Extracted from Ecotox databa	1. IUCLID Toxicity Data 2. Europe E	Not Available CHA Registered Substances - Ecotoxicological I CAquatic Hazard Assessment Data 6. NITE (Jap	nformation - Aquatic Toxicity 4.	US E

Ecotoxicity:

The tolerance of water organisms towards pH margin and variation is diverse. Recommended pH values for test species listed in OECD guidelines are between 6.0 and almost 9. Acute testing with fish showed 96h-LC50 at about pH 3.5

The likely reaction for beryllium in water is chemical speciation by which one species is converted to another. One such possible reaction in water is hydrolysis. Soluble beryllium salts in water are hydrolysed to form relatively insoluble beryllium hydroxide, which would have a low solubility in the pH range of most natural waters. Complexation with hydroxide ions to form soluble polynuclear hydroxide complexes is another possible reaction, although the pH range necessary for this reaction is probably not available in most natural waters. **DO NOT** discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW
Bioaccumulative potential		
Ingredient	Bioaccumulation	
	No Data available for all ingredients	
Mobility in soil		
Ingredient	Mobility	
	No Data available for all ingredients	

SECTION 13 Disposal considerations

Waste treatment methods	
Product / Packaging disposal	 Containers may still present a chemical hazard/ danger when empty. Return to supplier for reuse/ recycling if possible. Otherwise: If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. Where possible retain label warnings and SDS and observe all notices pertaining to the product. Recycle wherever possible. Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified. Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).

SECTION 14 Transport information

Labels Required Marine Pollutant NO HAZCHEM 2X

Land transport (ADG)

1 ()		
UN number or ID number	3264	
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid solution)	
Transport hazard class(es)	Class 8 Subsidiary risk Not Applicable	
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	Special provisions223 274Limited quantity5 L	

Air transport (ICAO-IATA / DGR)

UN number	3264		
UN proper shipping name	Corrosive liquid, acidic, inorganic, n.o.s. * (Nitric acid solution)		
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	8 Not Applicable 8L	
Packing group	Ш		
Environmental hazard	Not Applicable	Not Applicable	

	Special provisions	A3 A803
	Cargo Only Packing Instructions	856
	Cargo Only Maximum Qty / Pack	60 L
Special precautions for user	Passenger and Cargo Packing Instructions	852
	Passenger and Cargo Maximum Qty / Pack	5 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y841
	Passenger and Cargo Limited Maximum Qty / Pack	1 L

Sea transport (IMDG-Code / GGVSee)

UN number	3264	
UN proper shipping name	CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (Nitric acid solution)	
Transport hazard class(es)	IMDG Class 8 IMDG Subrisk Not Applicable	
Packing group	III	
Environmental hazard	Not Applicable	
Special precautions for user	EMS NumberF-A, S-BSpecial provisions223 274Limited Quantities5 L	

Transport in bulk according to Annex II of MARPOL and the IBC code Not Applicable

Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
beryllium acetate, basic	Not Available
nitric acid	Not Available
water	Not Available

Transport in bulk in accordance with the IGC Code

Product name	Ship Type
beryllium acetate, basic	Not Available
nitric acid	Not Available
water	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

beryllium acetate, basic is found on the following regulatory lists	
Chemical Footprint Project - Chemicals of High Concern List International Agency for Research on Cancer (IARC) - Agents Classified by I	
International Agency for Research on Cancer (IARC) - Agents Classified by the IARC	Monographs - Group 1: Carcinogenic to humans
Monographs	
nitric acid is found on the following regulatory lists	
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) -	Australian Inventory of Industrial Chemicals (AIIC)

water is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

National Inventory Status

Schedule 5

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	No (beryllium acetate, basic)
Canada - DSL	No (beryllium acetate, basic)
Canada - NDSL	No (beryllium acetate, basic; nitric acid; water)
China - IECSC	No (beryllium acetate, basic)
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	No (beryllium acetate, basic)
Korea - KECI	No (beryllium acetate, basic)
New Zealand - NZIoC	No (beryllium acetate, basic)
Philippines - PICCS	No (beryllium acetate, basic)
USA - TSCA	No (beryllium acetate, basic)

National Inventory	Status
Taiwan - TCSI	Yes
Mexico - INSQ	No (beryllium acetate, basic)
Vietnam - NCI	No (beryllium acetate, basic)
Russia - FBEPH	No (beryllium acetate, basic)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

SECTION 16 Other information

Revision Date	04/04/2023
Initial Date	04/04/2023

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-STEL: Permissible Concentration-Short Term Exposure Limit IARC: International Agency for Research on Cancer ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations ES: Exposure Standard OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value **BCF: BioConcentration Factors** BEI: Biological Exposure Index AIIC: Australian Inventory of Industrial Chemicals DSL: Domestic Substances List NDSL: Non-Domestic Substances List IECSC: Inventory of Existing Chemical Substance in China EINECS: European INventory of Existing Commercial chemical Substances ELINCS: European List of Notified Chemical Substances NLP: No-Longer Polymers ENCS: Existing and New Chemical Substances Inventory KECI: Korea Existing Chemicals Inventory NZIoC: New Zealand Inventory of Chemicals PICCS: Philippine Inventory of Chemicals and Chemical Substances TSCA: Toxic Substances Control Act TCSI: Taiwan Chemical Substance Inventory INSQ: Inventario Nacional de Sustancias Químicas NCI: National Chemical Inventory FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.