



# N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL

Novachem Pty Ltd

Chemwatch Hazard Alert Code: 4

Version No: 3.4

Safety Data Sheet according to WHS Regulations (Hazardous Chemicals) Amendment 2020 and ADG requirements

Issue Date: 18/07/2023

Print Date: 18/07/2023

S.GHS.AUS.EN

## SECTION 1 Identification of the substance / mixture and of the company / undertaking

### Product Identifier

Product name	N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL
Synonyms	Not Available
Proper shipping name	METHANOL
Other means of identification	ULM-6091-S

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	For professional use only
--------------------------	---------------------------

### Details of the manufacturer or supplier of the safety data sheet

Registered company name	Novachem Pty Ltd	Novachem Pty Ltd
Address	25 Crissane Road, Heidelberg West Victoria 3081 Australia	25 Crissane Road, Heidelberg West Victoria 3081 Australia
Telephone	+61384151255	+61384151255
Fax	+61386250088	+61386250088
Website	<a href="http://www.novachem.com.au">www.novachem.com.au</a>	<a href="http://www.novachem.com.au">www.novachem.com.au</a>
Email	<a href="mailto:novachem@novachem.com.au">novachem@novachem.com.au</a>	<a href="mailto:novachem@novachem.com.au">novachem@novachem.com.au</a>

### Emergency telephone number

Association / Organisation	Victorian Poisons Information Centre	Victorian Poisons Information Centre
Emergency telephone numbers	13 11 26	13 11 26
Other emergency telephone numbers	Not Available	Not Available

## SECTION 2 Hazards identification

### Classification of the substance or mixture

Poisons Schedule	Not Applicable
Classification [1]	Flammable Liquids Category 2, Acute Toxicity (Oral) Category 3, Acute Toxicity (Dermal) Category 3, Skin Corrosion/Irritation Category 2, Serious Eye Damage/Eye Irritation Category 2A, Acute Toxicity (Inhalation) Category 3, Reproductive Toxicity Category 1B, Specific Target Organ Toxicity - Single Exposure Category 1, Specific Target Organ Toxicity - Repeated Exposure Category 2
Legend:	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

### Label elements

Hazard pictogram(s)	
Signal word	Danger

### Hazard statement(s)

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H311	Toxic in contact with skin.
H315	Causes skin irritation.

**N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL**

H319	Causes serious eye irritation.
H331	Toxic if inhaled.
H360D	May damage the unborn child.
H370	Causes damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.

**Precautionary statement(s) Prevention**

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe mist/vapours/spray.
P264	Wash all exposed external body areas thoroughly after handling.

**Precautionary statement(s) Response**

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider.
P308+P311	IF exposed or concerned: Call a POISON CENTER/doctor/physician/first aider.
P330	Rinse mouth.
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.

**Precautionary statement(s) Storage**

P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.
------	--

**SECTION 3 Composition / information on ingredients****Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
67-56-1	99.8737	<u>methanol</u>
2632-86-2*	0.1263	<u>N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY</u>
<b>Legend:</b>	1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available	

**SECTION 4 First aid measures****Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Quickly but gently, wipe material off skin with a dry, clean cloth.</li> <li>▶ Immediately remove all contaminated clothing, including footwear.</li> <li>▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> </ul>
<b>Ingestion</b>	<ul style="list-style-type: none"> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Seek medical advice.</li> <li>▶ Avoid giving milk or oils.</li> <li>▶ Avoid giving alcohol.</li> <li>▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.</li> </ul>

Continued...

## N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL

### Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute and short term repeated exposures to methanol:

- Toxicity results from accumulation of formaldehyde/formic acid.
- Clinical signs are usually limited to CNS, eyes and GI tract. Severe metabolic acidosis may produce dyspnea and profound systemic effects which may become intractable. All symptomatic patients should have arterial pH measured. Evaluate airway, breathing and circulation.
- Stabilise obtunded patients by giving naloxone, glucose and thiamine.
- Decontaminate with Ipecac or lavage for patients presenting 2 hours post-ingestion. Charcoal does not absorb well; the usefulness of cathartic is not established.
- Forced diuresis is not effective; haemodialysis is recommended where peak methanol levels exceed 50 mg/dL (this correlates with serum bicarbonate levels below 18 mEq/L).
- Ethanol, maintained at levels between 100 and 150 mg/dL, inhibits formation of toxic metabolites and may be indicated when peak methanol levels exceed 20 mg/dL. An intravenous solution of ethanol in D5W is optimal.
- Folate, as leucovorin, may increase the oxidative removal of formic acid. 4-methylpyrazole may be an effective adjunct in the treatment. 8-Phenytoin may be preferable to diazepam for controlling seizure.

[Ellenhorn Barceloux: Medical Toxicology]

Methanol poisoning can be treated with fomepizole, or if unavailable, ethanol. Both drugs act to reduce the action of alcohol dehydrogenase on methanol by means of competitive inhibition. Ethanol, the active ingredient in alcoholic beverages, acts as a competitive inhibitor by more effectively binding and saturating the alcohol dehydrogenase enzyme in the liver, thus blocking the binding of methanol. Methanol is excreted by the kidneys without being converted into the very toxic metabolites formaldehyde and formic acid. Alcohol dehydrogenase instead enzymatically converts ethanol to acetaldehyde, a much less toxic organic molecule. Additional treatment may include sodium bicarbonate for metabolic acidosis, and hemodialysis or hemodiafiltration to remove methanol and formate from the blood. Folinic acid or folic acid is also administered to enhance the metabolism of formate.

#### BIOLOGICAL EXPOSURE INDEX - BEI

Determinant	Index	Sampling Time	Comment
1. Methanol in urine	15 mg/l	End of shift	B, NS
2. Formic acid in urine	80 mg/gm creatinine	Before the shift at end of workweek	B, NS

B: Background levels occur in specimens collected from subjects **NOT** exposed.

NS: Non-specific determinant - observed following exposure to other materials.

## SECTION 5 Firefighting measures

### Extinguishing media

Water may be an ineffective extinguishing media for methanol fires; static explosions are reported for aqueous solutions as dilute as 30%. Water may be used to cool containers.

- ▶ Alcohol stable foam.
- ▶ Dry chemical powder.
- ▶ BCF (where regulations permit).
- ▶ Carbon dioxide.

### Special hazards arising from the substrate or mixture

<b>Fire Incompatibility</b>	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

### Advice for firefighters

<b>Fire Fighting</b>	
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Liquid and vapour are highly flammable.</li> <li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li> <li>▶ Vapour may travel a considerable distance to source of ignition.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> </ul> Combustion products include: carbon dioxide (CO <sub>2</sub> ) formaldehyde other pyrolysis products typical of burning organic material.
<b>HAZCHEM</b>	•2WE

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> </ul>
<b>Major Spills</b>	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

<b>Safe handling</b>	<ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> </ul>
----------------------	--

Continued...

**N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL**

	<ul style="list-style-type: none"> <li>▶ Avoid all personal contact, including inhalation.</li> <li>▶ Wear protective clothing when risk of exposure occurs.</li> <li>▶ Use in a well-ventilated area.</li> <li>▶ Prevent concentration in hollows and sumps.</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ Store in original containers in approved flame-proof area.</li> <li>▶ No smoking, naked lights, heat or ignition sources.</li> <li>▶ <b>DO NOT store in pits, depression, basement or areas where vapours may be trapped.</b></li> <li>▶ Keep containers securely sealed.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Glass container is suitable for laboratory quantities</li> <li>▶ Packing as supplied by manufacturer.</li> <li>▶ Plastic containers may only be used if approved for flammable liquid.</li> <li>▶ Check that containers are clearly labelled and free from leaks.</li> <li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>▶ For manufactured product having a viscosity of at least 250 cSt.</li> </ul>
<b>Storage incompatibility</b>	<p>Methanol:</p> <ul style="list-style-type: none"> <li>▶ reacts violently with strong oxidisers, acetyl bromide, alkyl aluminium salts, beryllium dihydride, bromine, chromic acid, 1-chloro-3,3-difluoro-2-methoxycyclopropene, cyanuric chloride, diethylzinc, isophthaloyl chloride, nitric acid, perchloric acid, potassium-tert-butoxide, potassium sulfur diimide, Raney nickel catalysts, 2,4,6-trichlorotriazine, triethylaluminium, 1,3,3-trifluoro-2-methoxycyclopropene</li> <li>▶ is incompatible with strong acids, strong caustics, alkaline earth and alkali metals, aliphatic amines, acetaldehyde, benzoyl peroxide, 1,3-bis(di-n-cyclopentadienyl iron)-2-propen-1-one, calcium carbide, chloroform, chromic anhydride, chromium trioxide, dialkylzinc, dichlorine oxide, dichloromethane, ethylene oxide, hypochlorous acid, isocyanates, isopropyl chlorocarbonate, lithium tetrahydroaluminate, magnesium, methyl azide, nitrogen dioxide, palladium, pentafluoroguanidine, perchloryl fluoride, phosphorus pentasulfide, phosphorus trioxide, potassium, tangerine oil, triisobutylaluminium</li> <li>▶ mixtures with lead perchlorate, sodium hypochlorite are explosive</li> <li>▶ may react with metallic aluminium at high temperatures</li> <li>▶ slowly corrodes lead and aluminium</li> <li>▶ may generate electrostatic charges, due to low conductivity, on flow or agitation</li> <li>▶ attacks some plastics, rubber and coatings.</li> </ul> <p>Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content</p> <p>Alcohols</p> <ul style="list-style-type: none"> <li>▶ are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.</li> <li>▶ reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen</li> <li>▶ react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzinc, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium</li> <li>▶ should not be heated above 49 deg. C. when in contact with aluminium equipment</li> <li>▶ Avoid storage with reducing agents.</li> </ul>

**SECTION 8 Exposure controls / personal protection**

**Control parameters**

**Occupational Exposure Limits (OEL)**

**INGREDIENT DATA**

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
Australia Exposure Standards	methanol	Methyl alcohol	200 ppm / 262 mg/m3	328 mg/m3 / 250 ppm	Not Available	Not Available

**Emergency Limits**

Ingredient	TEEL-1	TEEL-2	TEEL-3
methanol	Not Available	Not Available	Not Available

Ingredient	Original IDLH	Revised IDLH
methanol	6,000 ppm	Not Available
N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY	Not Available	Not Available

**Occupational Exposure Banding**


Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY	E	≤ 0.1 ppm

<b>Notes:</b>	<i>Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.</i>
---------------	---

**Exposure controls**

<b>Appropriate engineering controls</b>	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.
---	--

## N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL

	The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Safety glasses with side shields.</li> <li>▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care.</p>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot and shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.</li> </ul>

### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

**"Forsberg Clothing Performance Index".**

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL

Material	CPI
BUTYL	A
BUTYL/NEOPRENE	A
PE/EVAL/PE	A
PVDC/PE/PVDC	A
SARANEX-23	A
SARANEX-23 2-PLY	A
TEFLON	A
VITON/NEOPRENE	A
NEOPRENE	B
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
PVA	C
PVC	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

### Respiratory protection

Type AX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 5 x ES	AX-AUS / Class 1	-	AX-PAPR-AUS / Class 1
up to 25 x ES	Air-line*	AX-2	AX-PAPR-2
up to 50 x ES	-	AX-3	-
50+ x ES	-	Air-line**	-

\* - Continuous-flow; \*\* - Continuous-flow or positive pressure demand

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AX-AUS / Class 1	-

Continued...

**N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000  
UG/ML IN METHANOL**

up to 50	1000	-	AX-AUS / Class 1
up to 50	5000	Airline *	-
up to 100	5000	-	AX-2
up to 100	10000	-	AX-3
100+		-	Airline**

\*\* - Continuous-flow or positive pressure demand.

A(All classes) = Organic vapours, B AUS or B1 = Acid gases, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 deg C)

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

<b>Appearance</b>	Colourless liquid		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	0.791
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	455
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature (°C)</b>	Not Available
<b>Melting point / freezing point (°C)</b>	-98	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	64.7	<b>Molecular weight (g/mol)</b>	32.04
<b>Flash point (°C)</b>	9.7	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	HIGHLY FLAMMABLE.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	36	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	6	<b>Volatile Component (%vol)</b>	>99
<b>Vapour pressure (kPa)</b>	13.03	<b>Gas group</b>	Not Available
<b>Solubility in water</b>	Miscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	1.11	<b>VOC g/L</b>	Not Available

## SECTION 10 Stability and reactivity

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Static induced flash fires have happened when filling plastic containers with methanol / water solutions with as low as 30% methanol content.</li> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 Toxicological information

### Information on toxicological effects

<b>Inhaled</b>	<p>Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects. The material is not thought to produce respiratory irritation (as classified by EC Directives using animal models). Nevertheless inhalation of vapours, fumes or aerosols, especially for prolonged periods, may produce respiratory discomfort and occasionally, distress.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo.</p>
----------------	--

**N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL**

	<p>Minor but regular methanol exposures may effect the central nervous system, optic nerves and retinae. Symptoms may be delayed, with headache, fatigue, nausea, blurring of vision and double vision. Continued or severe exposures may cause damage to optic nerves, which may become severe with permanent visual impairment even blindness resulting.</p> <p><b>WARNING:</b> Methanol is only slowly eliminated from the body and should be regarded as a cumulative poison which cannot be made non-harmful [CCINFO]</p>
<b>Ingestion</b>	<p><b>Toxic effects</b> may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual.</p> <p>Methanol may produce a burning or painful sensation in the mouth, throat, chest, and stomach. This may be accompanied by nausea, vomiting, headache, dizziness, shortness of breath, weakness, fatigue, leg cramps, restlessness, confusion, drunken behaviour, visual disturbance, drowsiness, coma and death. 60-200 ml of methanol is a fatal dose for most adults with as little as 10 ml producing blindness. In massive overdose, liver, kidney, heart and muscle injury have been described.</p> <p>Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)</p>
<b>Skin Contact</b>	<p>Skin contact with the material may produce toxic effects; systemic effects may result following absorption.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p> <p>There is strong evidence to suggest that this material, on a single contact with skin, can cause serious, irreversible damage of organs.</p> <p>There is some evidence to suggest that the material may cause moderate inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.</p>
<b>Eye</b>	<p>Methanol is a mild to moderate eye irritant. High vapor concentration or liquid contact with eyes causes irritation, tearing, and burning.</p> <p>Direct contact of the eye with ethanol may cause immediate stinging and burning with reflex closure of the lid and tearing, transient injury of the corneal epithelium and hyperaemia of the conjunctiva.</p> <p>There is some evidence that material may produce eye irritation in some persons and produce eye damage 24 hours or more after instillation. Moderate inflammation may be expected with redness; conjunctivitis may occur with prolonged exposure.</p>
<b>Chronic</b>	<p>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>This material can cause serious damage if one is exposed to it for long periods. It can be assumed that it contains a substance which can produce severe defects.</p> <p>Ample evidence exists, from results in experimentation, that developmental disorders are directly caused by human exposure to the material. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. Liver and/or kidney injury may also result.</p>

<b>N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available
<b>methanol</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Dermal (rabbit) LD50: 15800 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg/24h-moderate
	Inhalation(Rat) LC50: 64000 ppm4h <sup>[2]</sup>	Eye (rabbit): 40 mg-moderate
	Oral (Rat) LD50: 5628 mg/kg <sup>[2]</sup>	Eye: no adverse effect observed (not irritating) <sup>[1]</sup>
		Skin (rabbit): 20 mg/24 h-moderate
	Skin: no adverse effect observed (not irritating) <sup>[1]</sup>	
<b>N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY</b>	<b>TOXICITY</b>	<b>IRRITATION</b>
	Not Available	Not Available

**Legend:** 1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

<b>METHANOL</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.		
<b>Acute Toxicity</b>	✓	<b>Carcinogenicity</b>	✗
<b>Skin Irritation/Corrosion</b>	✓	<b>Reproductivity</b>	✓
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✓
<b>Respiratory or Skin sensitisation</b>	✗	<b>STOT - Repeated Exposure</b>	✓
<b>Mutagenicity</b>	✗	<b>Aspiration Hazard</b>	✗

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
 ✓ – Data available to make classification

## SECTION 12 Ecological information

### Toxicity

<b>N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL</b>	<b>Endpoint</b>	<b>Test Duration (hr)</b>	<b>Species</b>	<b>Value</b>	<b>Source</b>
	Not Available	Not Available	Not Available	Not Available	Not Available

Continued...

**N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL**

methanol	Endpoint	Test Duration (hr)	Species	Value	Source
	EC50	48h	Crustacea	>10000mg/l	2
	EC50	96h	Algae or other aquatic plants	14.11-20.623mg/l	4
	LC50	96h	Fish	290mg/l	2
	NOEC(ECx)	720h	Fish	0.007mg/L	4
N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available

**Legend:**

Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data

For Methanol: Log Kow: -0.82 to -0.66; Koc: 1; Henry s Law Constant: 4.55x10<sup>-6</sup> atm-cu m/mole; Vapor Pressure: 127 mm Hg; BCF: < 10.

Atmospheric Fate: Methanol is expected to exist solely as a vapor in the ambient atmosphere. Vapor-phase methanol is broken down in the atmosphere by reactions with hydroxyl radicals; the half-life for this reaction in air is estimated to be 17 days.

Terrestrial Fate: Methanol is expected to have very high mobility in soil.

**DO NOT discharge into sewer or waterways.**

**Persistence and degradability**

Ingredient	Persistence: Water/Soil	Persistence: Air
methanol	LOW	LOW

**Bioaccumulative potential**

Ingredient	Bioaccumulation
methanol	LOW (BCF = 10)


**Mobility in soil**

Ingredient	Mobility
methanol	HIGH (KOC = 1)

**SECTION 13 Disposal considerations****Waste treatment methods**

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li> </ul> <p>Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.</p> <p>A Hierarchy of Controls seems to be common - the user should investigate:</p> <ul style="list-style-type: none"> <li>▶ Reduction</li> <li>▶ Reuse</li> <li>▶ Recycling</li> <li>▶ Disposal (if all else fails)</li> </ul> <p>This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.</p> <ul style="list-style-type: none"> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> <li>▶ In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li> <li>▶ Where in doubt contact the responsible authority.</li> <li>▶ Recycle wherever possible.</li> <li>▶ Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> <li>▶ Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> <li>▶ Decontaminate empty containers.</li> </ul>
-------------------------------------	--

**SECTION 14 Transport information****Labels Required**

	
<b>Marine Pollutant</b>	NO
<b>HAZCHEM</b>	*2WE

**Land transport (ADG)**

Continued...

**N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL**

<b>UN number or ID number</b>	1230	
<b>UN proper shipping name</b>	METHANOL	
<b>Transport hazard class(es)</b>	Class	3
	Subsidiary risk	Not Applicable
<b>Packing group</b>	II	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	Special provisions	279
	Limited quantity	1 L

**Air transport (ICAO-IATA / DGR)**

<b>UN number</b>	1230	
<b>UN proper shipping name</b>	Methanol	
<b>Transport hazard class(es)</b>	ICAO/IATA Class	3
	ICAO / IATA Subrisk	Not Applicable
	ERG Code	3L
<b>Packing group</b>	II	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	Special provisions	A113
	Cargo Only Packing Instructions	364
	Cargo Only Maximum Qty / Pack	60 L
	Passenger and Cargo Packing Instructions	352
	Passenger and Cargo Maximum Qty / Pack	1 L
	Passenger and Cargo Limited Quantity Packing Instructions	Y341
	Passenger and Cargo Limited Maximum Qty / Pack	1 L

**Sea transport (IMDG-Code / GGVSee)**

<b>UN number</b>	1230	
<b>UN proper shipping name</b>	METHANOL	
<b>Transport hazard class(es)</b>	IMDG Class	3
	IMDG Subrisk	Not Applicable
<b>Packing group</b>	II	
<b>Environmental hazard</b>	Not Applicable	
<b>Special precautions for user</b>	EMS Number	F-E, S-D
	Special provisions	279
	Limited Quantities	1 L

**Transport in bulk according to Annex II of MARPOL and the IBC code**

Not Applicable

**Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

Product name	Group
methanol	Not Available
N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY	Not Available

**Transport in bulk in accordance with the IGC Code**

Product name	Ship Type
methanol	Not Available
N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY	Not Available

**SECTION 15 Regulatory information**

Safety, health and environmental regulations / legislation specific for the substance or mixture

Continued...

## N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000 UG/ML IN METHANOL

### methanol is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals  
Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6  
Australian Inventory of Industrial Chemicals (AIIC)  
Chemical Footprint Project - Chemicals of High Concern List

### N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY is found on the following regulatory lists

Not Applicable

### National Inventory Status

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Canada - DSL	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Canada - NDSL	No (methanol; N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
China - IECSC	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Europe - EINEC / ELINCS / NLP	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Japan - ENCS	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Korea - KECI	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
New Zealand - NZIoC	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Philippines - PICCS	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
USA - TSCA	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Taiwan - TCSI	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Mexico - INSQ	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Vietnam - NCI	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
Russia - FBEPH	No (N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT UNLABELED 90% CHEMICAL PURITY)
<b>Legend:</b>	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.

### SECTION 16 Other information

<b>Revision Date</b>	18/07/2023
<b>Initial Date</b>	07/12/2020

### SDS Version Summary

Version	Date of Update	Sections Updated
2.4	18/07/2023	Hazards identification - Classification, Accidental release measures - Spills (major)

### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### Definitions and abbreviations

PC - TWA: Permissible Concentration-Time Weighted Average  
PC - STEL: Permissible Concentration-Short Term Exposure Limit  
IARC: International Agency for Research on Cancer  
ACGIH: American Conference of Governmental Industrial Hygienists  
STEL: Short Term Exposure Limit  
TEEL: Temporary Emergency Exposure Limit  
IDLH: Immediately Dangerous to Life or Health Concentrations  
ES: Exposure Standard  
OSF: Odour Safety Factor  
NOAEL :No Observed Adverse Effect Level  
LOAEL: Lowest Observed Adverse Effect Level  
TLV: Threshold Limit Value  
LOD: Limit Of Detection  
OTV: Odour Threshold Value  
BCF: BioConcentration Factors  
BEI: Biological Exposure Index  
AIIC: Australian Inventory of Industrial Chemicals  
DSL: Domestic Substances List  
NDSL: Non-Domestic Substances List  
IECSC: Inventory of Existing Chemical Substance in China  
EINECS: European Inventory of Existing Commercial chemical Substances  
ELINCS: European List of Notified Chemical Substances  
NLP: No-Longer Polymers  
ENCS: Existing and New Chemical Substances Inventory  
KECI: Korea Existing Chemicals Inventory  
NZIoC: New Zealand Inventory of Chemicals  
PICCS: Philippine Inventory of Chemicals and Chemical Substances  
TSCA: Toxic Substances Control Act  
TCSI: Taiwan Chemical Substance Inventory  
INSQ: Inventario Nacional de Sustancias Químicas

**N,N-DIMETHYLPHOSPHORAMIDIC ACID, MONOETHYL ESTER, SODIUM SALT (90% CP) UNL 1000  
UG/ML IN METHANOL**

NCI: National Chemical Inventory

FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

Powered by AuthorITe, from Chemwatch.